

# Lubrication Engineers LE 452 ALMASOL Chain & Cable Medium

**Lubrication Engineers NZ Ltd** 

Chemwatch Hazard Alert Code:

Issue Date: 23/12/2022 Print Date: 29/10/2024 S.GHS.NZL.EN

Version No: **8.1**Safety Data Sheet according to the Health and Safety at Work (Hazardous Substances) Regulations 2017

## SECTION 1 Identification of the substance / mixture and of the company / undertaking

#### **Product Identifier**

Chemwatch: 4743-55

Product name	Lubrication Engineers LE 452 ALMASOL Chain & Cable Medium		
Chemical Name	Not Applicable		
Synonyms	Not Available		
Chemical formula	Not Applicable		
Other means of identification	Not Available		

## Relevant identified uses of the substance or mixture and uses advised against

Relevant identified uses	Lubricant
Relevant identified uses	Use according to manufacturer's directions.

#### Details of the manufacturer or supplier of the safety data sheet

Registered company name	Lubrication Engineers NZ Ltd				
Address	1F Piermark Drive North Harbour Industrial Estate Albany, Auckland New Zealand				
Telephone	+64 09 415 9411				
Fax	+64 09 4158411				
Website	Not Available				
Email	Not Available				

## **Emergency telephone number**

Association / Organisation	Lubrication Engineers NZ Ltd	CHEMWATCH EMERGENCY RESPONSE (24/7)
Emergency telephone number(s)	+64 21 3385487	+64 800 700 112
Other emergency telephone number(s)	Not Available	+61 3 9573 3188

Once connected and if the message is not in your preferred language then please dial 01

#### **SECTION 2 Hazards identification**

#### Classification of the substance or mixture

Not considered a Hazardous Substance according to the criteria of the New Zealand Hazardous Substances New Organisms legislation. Not regulated for transport of Dangerous Goods.

#### Chemwatch Hazard Ratings

		Min	Max	
Flammability	1			
Toxicity	0			
Body Contact	1			0 = Minimum 1 = Low
Reactivity	1			2 = Moderate
Chronic	0			3 = High 4 = Extreme

Classification <sup>[1]</sup>	Non hazardous
Legend:	1. Classified by Chemwatch; 2. Classification drawn from CCID EPA NZ; 3. Classification drawn from Regulation (EU) No 1272/2008 - Annex VI

Chemwatch: **4743-55** Page **2** of **11** 

Version No: 8.1

#### Lubrication Engineers LE 452 ALMASOL Chain & Cable Medium

Issue Date: 23/12/2022 Print Date: 29/10/2024

Determined by Chemwatch using GHS/HSNO criteria

Not Available

#### Label elements

Hazard pictogram(s)

Not Applicable

Signal word

Not Applicable

#### Hazard statement(s)

Not Applicable

#### Precautionary statement(s) Prevention

Not Applicable

## Precautionary statement(s) Response

Not Applicable

#### Precautionary statement(s) Storage

Not Applicable

#### Precautionary statement(s) Disposal

Not Applicable

## **SECTION 3 Composition / information on ingredients**

#### Substances

See section below for composition of Mixtures

#### **Mixtures**

CAS No	%[weight]	Name		
12001-26-2	NotSpec	<u>mica</u>		
Not Available	NotSpec	pigment as		
13463-67-7		titanium dioxide		
1309-37-1	NotSpec	ferric oxide		
Not Available	100	Ingredients determined not to be hazardous		
Legend: 1. Classified by Chemwatch; 2. Classification drawn from CCID EPA NZ; 3. Classification drawn from Regulation (EU) No 1272/2008 - Annex VI: 4. Classification drawn from C&L: * EU IOELVs available				

## **SECTION 4 First aid measures**

#### Description of first aid measures

Eye Contact	If this product comes in contact with eyes:  • Wash out immediately with water.  • If irritation continues, seek medical attention.  • Removal of contact lenses after an eye injury should only be undertaken by skilled personnel.
Skin Contact	If skin or hair contact occurs:  ► Flush skin and hair with running water (and soap if available).  ► Seek medical attention in event of irritation.
Inhalation	<ul> <li>If fumes, aerosols or combustion products are inhaled remove from contaminated area.</li> <li>Other measures are usually unnecessary.</li> </ul>
Ingestion	<ul> <li>Immediately give a glass of water.</li> <li>First aid is not generally required. If in doubt, contact a Poisons Information Centre or a doctor.</li> </ul>

## Indication of any immediate medical attention and special treatment needed

Treat symptomatically.

- Heavy and persistent skin contamination over many years may lead to dysplastic changes. Pre-existing skin disorders may be aggravated by exposure to this product.
- In general, emesis induction is unnecessary with high viscosity, low volatility products, i.e. most oils and greases.
- High pressure accidental injection through the skin should be assessed for possible incision, irrigation and/or debridement.

**NOTE:** Injuries may not seem serious at first, but within a few hours tissue may become swollen, discoloured and extremely painful with extensive subcutaneous necrosis. Product may be forced through considerable distances along tissue planes.

Chemwatch: **4743-55** Page **3** of **11** 

Version No: 8.1

#### Lubrication Engineers LE 452 ALMASOL Chain & Cable Medium

Issue Date: **23/12/2022**Print Date: **29/10/2024** 

## **SECTION 5 Firefighting measures**

#### **Extinguishing media**

- Alcohol stable foam.
- Dry chemical powder.
- ▶ BCF (where regulations permit).
- Carbon dioxide.

Do not use a water jet to fight fire.

#### Special hazards arising from the substrate or mixture

Fire Incompatibility

Avoid contamination with oxidising agents i.e. nitrates, oxidising acids, chlorine bleaches, pool chlorine etc. as ignition may
result

#### Advice for firefighters

Advice for inteligities						
Fire Fighting	<ul> <li>Alert Fire Brigade and tell them location and nature of hazard.</li> <li>Wear full body protective clothing with breathing apparatus.</li> <li>Prevent, by any means available, spillage from entering drains or water course.</li> <li>Use water delivered as a fine spray to control fire and cool adjacent area.</li> </ul>					
Fire/Explosion Hazard	<ul> <li>Combustible.</li> <li>Slight fire hazard when exposed to heat or flame.</li> <li>Heating may cause expansion or decomposition leading to violent rupture of containers.</li> <li>On combustion, may emit toxic fumes of carbon monoxide (CO).</li> <li>Combustion products include:         <ul> <li>carbon dioxide (CO2)</li> </ul> </li> <li>other pyrolysis products typical of burning organic material.</li> <li>May emit poisonous fumes.</li> <li>CARE: Water in contact with hot liquid may cause foaming and a steam explosion with wide scattering of hot oil and possible severe burns. Foaming may cause overflow of containers and may result in possible fire.</li> </ul>					

#### **SECTION 6 Accidental release measures**

## Personal precautions, protective equipment and emergency procedures

See section 8

## **Environmental precautions**

See section 12

#### Methods and material for containment and cleaning up

Minor Spills	Slippery when spilt.  Remove all ignition sources.  Clean up all spills immediately.  Avoid breathing vapours and contact with skin and eyes.  Control personal contact with the substance, by using protective equipment.
Major Spills	Slippery when spilt.  Moderate hazard.  Clear area of personnel and move upwind.  Alert Fire Brigade and tell them location and nature of hazard.  Wear breathing apparatus plus protective gloves.

Personal Protective Equipment advice is contained in Section 8 of the SDS.

## **SECTION 7 Handling and storage**

#### Precautions for safe handling

Precautions for safe handling				
Safe handling	<ul> <li>Avoid all personal contact, including inhalation.</li> <li>Wear protective clothing when risk of exposure occurs.</li> <li>Use in a well-ventilated area.</li> <li>Prevent concentration in hollows and sumps.</li> </ul>			
Other information	<ul> <li>Store in original containers.</li> <li>Keep containers securely sealed.</li> <li>No smoking, naked lights or ignition sources.</li> <li>Store in a cool, dry, well-ventilated area.</li> </ul>			

## Conditions for safe storage, including any incompatibilities

#### Suitable container

- Metal can or drum
- Packaging as recommended by manufacturer.

Page 4 of 11

Chemwatch: 4743-55 Version No: 8.1

#### Lubrication Engineers LE 452 ALMASOL Chain & Cable Medium

Issue Date: 23/12/2022 Print Date: 29/10/2024

Storage incompatibility

- Check all containers are clearly labelled and free from leaks.
- ▶ Avoid reaction with oxidising agents
- Avoid strong acids, bases.















X — Must not be stored together

0 — May be stored together with specific preventions

+ — May be stored together

Note: Depending on other risk factors, compatibility assessment based on the table above may not be relevant to storage situations, particularly where large volumes of dangerous goods are stored and handled. Reference should be made to the Safety Data Sheets for each substance or article and risks assessed accordingly.

#### SECTION 8 Exposure controls / personal protection

#### **Control parameters**

Occupational Exposure Limits (OEL)

#### INGREDIENT DATA

Source	Ingredient	Material name	TWA	STEL	Peak	Notes
New Zealand Workplace Exposure Standards (WES)	mica	Mica respirable dust	3 mg/m3	Not Available	Not Available	Not Available
New Zealand Workplace Exposure Standards (WES)	titanium dioxide	Titanium dioxide	10 mg/m3	Not Available	Not Available	Not Available
New Zealand Workplace Exposure Standards (WES)	ferric oxide	Iron oxide dust and fume (Fe2O3), as Fe	5 mg/m3	Not Available	Not Available	(w) - A range of airborne contaminants are associated with gas and arc welding. The type of metal being welded, the electrode employed and the welding process will all influence the composition and amount of fume. Gaseous products such as oxides of nitrogen, carbon monoxide and ozone may also be produced. Exposure assessment of welding fume should be based on measurement of known or expected components in welding fume which would include metal constituents as well as shielding gases and contaminants produced during combustion of surface coatings and cleaning products, where present
New Zealand Workplace Exposure Standards (WES)	ferric oxide	Rouge	10 mg/m3	Not Available	Not Available	(w) - A range of airborne contaminants are associated with gas and arc welding. The type of metal being welded, the electrode employed and the welding process will all influence the composition and amount of fume. Gaseous products such as oxides of nitrogen, carbon monoxide and ozone may also be produced. Exposure assessment of welding fume should be based on measurement of known or expected components in welding fume which would include metal constituents as well as shielding gases and contaminants produced during combustion of surface coatings and cleaning products, where present

Ingredient	Original IDLH	Revised IDLH
mica	1,500 mg/m3	Not Available
titanium dioxide	5,000 mg/m3	Not Available
ferric oxide	2,500 mg/m3	Not Available

#### **Exposure controls**

## Appropriate engineering controls

Engineering controls are used to remove a hazard or place a barrier between the worker and the hazard. Well-designed engineering controls can be highly effective in protecting workers and will typically be independent of worker interactions to provide this high level of protection.

The basic types of engineering controls are:

Process controls which involve changing the way a job activity or process is done to reduce the risk.

Enclosure and/or isolation of emission source which keeps a selected hazard "physically" away from the worker and ventilation that strategically "adds" and "removes" air in the work environment.

Chemwatch: 4743-55 Version No: 8.1

#### Lubrication Engineers LE 452 ALMASOL Chain & Cable Medium

Issue Date: 23/12/2022 Print Date: 29/10/2024

Individual protection measures, such as personal protective equipment	
Eye and face protection	<ul> <li>Safety glasses with side shields</li> <li>Chemical goggles.</li> <li>Contact lenses may pose a special hazard; soft contact lenses may absorb and concentrate irritants. A written policy document, describing the wearing of lenses or restrictions on use, should be created for each workplace or task. This should include a review of lens absorption and adsorption for the class of chemicals in use and an account of injury experience.</li> </ul>
Skin protection	See Hand protection below
Hands/feet protection	The selection of suitable gloves does not only depend on the material, but also on further marks of quality which vary from manufacturer to manufacturer. Where the chemical is a preparation of several substances, the resistance of the glove material can not be calculated in advance and has therefore to be checked prior to the application.  The exact break through time for substances has to be obtained from the manufacturer of the protective gloves and has to be observed when making a final choice.  Personal hygiene is a key element of effective hand care.  • Wear chemical protective gloves, e.g. PVC.  • Wear safety footwear or safety gumboots, e.g. Rubber
Body protection	See Other protection below
Other protection	<ul> <li>Overalls.</li> <li>P.V.C apron.</li> <li>Barrier cream.</li> <li>Skin cleansing cream.</li> </ul>

## Respiratory protection

- Cartridge respirators should never be used for emergency ingress or in areas of unknown vapour concentrations or oxygen content.
- The wearer must be warned to leave the contaminated area immediately on detecting any odours through the respirator. The odour may indicate that the mask is not functioning properly, that the vapour concentration is too high, or that the mask is not properly fitted. Because of these limitations, only restricted use of cartridge respirators is considered appropriate.
- Cartridge performance is affected by humidity. Cartridges should be changed after 2 hr of continuous use unless it is determined that the humidity is less than 75%, in which case, cartridges can be used for 4 hr. Used cartridges should be discarded daily, regardless of the length of time used

## **SECTION 9 Physical and chemical properties**

Appearance	Red/brown paste with a hydrocarbon odour; not miscible with water.		
Physical state	Non Slump Paste	Relative density (Water = 1)	0.95
Odour	Not Available	Partition coefficient n- octanol / water	Not Available
Odour threshold	Not Available	Auto-ignition temperature (°C)	Not Available
pH (as supplied)	6-8	Decomposition temperature (°C)	Not Available
Melting point / freezing point (°C)	Not Available	Viscosity (cSt)	Not Available
Initial boiling point and boiling range (°C)	Not Available	Molecular weight (g/mol)	Not Applicable
Flash point (°C)	203	Taste	Not Available
Evaporation rate	Not Available	Explosive properties	Not Available
Flammability	Not Applicable	Oxidising properties	Not Available
Upper Explosive Limit (%)	Not Available	Surface Tension (dyn/cm or mN/m)	Not Available
Lower Explosive Limit (%)	Not Available	Volatile Component (%vol)	Not Available
Vapour pressure (kPa)	Not Available	Gas group	Not Available
Solubility in water	Immiscible	pH as a solution (1%)	Not Available
Vapour density (Air = 1)	<1	VOC g/L	Not Available
Heat of Combustion (kJ/g)	Not Available	Ignition Distance (cm)	Not Available
Flame Height (cm)	Not Available	Flame Duration (s)	Not Available
Enclosed Space Ignition Time Equivalent (s/m3)	Not Available	Enclosed Space Ignition Deflagration Density (g/m3)	Not Available

Chemwatch: 4743-55 Page 6 of 11 Version No: 8.1 Lubrication Engineers LE 452 ALMASOL Chain & Cable Medium

#### **SECTION 10 Stability and reactivity**

Reactivity	See section 7
Chemical stability	<ul> <li>Unstable in the presence of incompatible materials.</li> <li>Product is considered stable.</li> <li>Hazardous polymerisation will not occur.</li> </ul>
Possibility of hazardous reactions	See section 7
Conditions to avoid	See section 7
Incompatible materials	See section 7
Hazardous decomposition products	See section 5

#### **SECTION 11 Toxicological information**

Lubrication Engineers LE

Inhaled	There is some evidence to suggest that the material can cause respiratory irritation in some persons. The body's response to such irritation can cause further lung damage.  Inhalation hazard is increased at higher temperatures.  Inhalation of oil droplets or aerosols may cause discomfort and may produce chemical inflammation of the lungs.
Ingestion	The material has <b>NOT</b> been classified by EC Directives or other classification systems as "harmful by ingestion". This is because of the lack of corroborating animal or human evidence.
Skin Contact	There is some evidence to suggest that this material can cause inflammation of the skin on contact in some persons.  The material may accentuate any pre-existing dermatitis condition  Open cuts, abraded or irritated skin should not be exposed to this material
Eye	There is some evidence to suggest that this material can cause eye irritation and damage in some persons.
Chronic	Substance accumulation, in the human body, may occur and may cause some concern following repeated or long-term occupational exposure.  Oil may contact the skin or be inhaled. Extended exposure can lead to eczema, inflammation of hair follicles, pigmentation of the face and warts on the soles of the feet.

Not Available	Not Available
TOXICITY	IRRITATION
Not Available	Not Available
TOXICITY	IRRITATION
dermal (hamster) LD50: >=10000 mg/kg <sup>[2]</sup>	Eye: no adverse effect observed (not irritating) <sup>[1]</sup>
Inhalation (Rat) LC50: >2.28 mg/l4h <sup>[1]</sup>	Skin (Human): 300ug/3D (intermittent) - Mild
Oral (Rat) LD50: >=2000 mg/kg <sup>[1]</sup>	Skin: no adverse effect observed (not irritating) $^{[1]}$
TOXICITY	IRRITATION
Oral (Rat) LD50: >5000 mg/kg <sup>[1]</sup>	Eye: no adverse effect observed (not irritating) <sup>[1]</sup>
	Skin: no adverse effect observed (not irritating) <sup>[1]</sup>
	TOXICITY  Not Available  TOXICITY  dermal (hamster) LD50: >=10000 mg/kg <sup>[2]</sup> Inhalation (Rat) LC50: >2.28 mg/l4h <sup>[1]</sup> Oral (Rat) LD50: >=2000 mg/kg <sup>[1]</sup> TOXICITY

Legend:

1. Value obtained from Europe ECHA Registered Substances - Acute toxicity 2. Value obtained from manufacturer's SDS. Unless otherwise specified data extracted from RTECS - Register of Toxic Effect of chemical Substances

IRRITATION

## \* IUCLID

TOXICITY

Laboratory (in vitro) and animal studies show, exposure to the material may result in a possible risk of irreversible effects, with the possibility of producing mutation.

## TITANIUM DIOXIDE

Exposure to titanium dioxide is via inhalation, swallowing or skin contact. When inhaled, it may deposit in lung tissue and lymph nodes causing dysfunction of the lungs and immune system. Absorption by the stomach and intestines depends on the size of the particle. It penetrated only the outermost layer of the skin, suggesting that healthy skin may be an effective barrier. The material may produce moderate eye irritation leading to inflammation. Repeated or prolonged exposure to irritants may produce conjunctivitis.

The material may cause skin irritation after prolonged or repeated exposure and may produce on contact skin redness, swelling, the production of vesicles, scaling and thickening of the skin.

WARNING: This substance has been classified by the IARC as Group 2B: Possibly Carcinogenic to Humans.

#### **MICA & TITANIUM DIOXIDE** & FERRIC OXIDE

Asthma-like symptoms may continue for months or even years after exposure to the material ends. This may be due to a nonallergic condition known as reactive airways dysfunction syndrome (RADS) which can occur after exposure to high levels of

Issue Date: 23/12/2022

Print Date: 29/10/2024

Version No: **8.1** 

## Lubrication Engineers LE 452 ALMASOL Chain & Cable Medium

Issue Date: 23/12/2022 Print Date: 29/10/2024

	highly irritating compound. Main criteria for diagnosing RADS include the absence of previous airways disease in a non-atopic individual, with sudden onset of persistent asthma-like symptoms within minutes to hours of a documented exposure to the irritant. Other criteria for diagnosis of RADS include a reversible airflow pattern on lung function tests, moderate to severe bronchial hyperreactivity on methacholine challenge testing, and the lack of minimal lymphocytic inflammation, without eosinophilia.		
MICA & TITANIUM DIOXIDE	No significant acute toxicological data identified	I in literature search.	
Acute Toxicity	×	Carcinogenicity	×
Skin Irritation/Corrosion	×	Reproductivity	×
Serious Eye Damage/Irritation	×	STOT - Single Exposure	×
Respiratory or Skin sensitisation	×	STOT - Repeated Exposure	×
Mutagenicity	×	Aspiration Hazard	×

Legend:

🗶 – Data either not available or does not fill the criteria for classification

✓ – Data available to make classification

## **SECTION 12 Ecological information**

## **Toxicity**

ubrication Engineers LE	Endpoint	Test Duration (hr)	Species	Value	Source
452 ALMASOL Chain & Cable Medium	Not Available	Not Available	Not Available	Not Available	Not Available
	Endpoint	Test Duration (hr)	Species	Value	Source
mica	Not Available	Not Available	Not Available	Not Available	Not Available
	Endpoint	Test Duration (hr)	Species	Value	Source
	BCF	1008h	Fish	<1.1-9.6	7
titanium dioxide	EC50	72h	Algae or other aquatic plants	3.75- 7.58mg/l	4
	EC50	48h	Crustacea	1.9mg/l	2
	LC50	96h	Fish	1.85- 3.06mg/l	4
	NOEC(ECx)	672h	Fish	>=0.004mg/L	2
	EC50	96h	Algae or other aquatic plants	179.05mg/l	2
	Endpoint	Test Duration (hr)	Species	Value	Source
	EC50	72h	Algae or other aquatic plants	18mg/l	2
ferric oxide	EC50	48h	Crustacea	>100mg/l	2
	NOEC(ECx)	504h	Fish	0.52mg/l	2
	LC50	96h	Fish	0.05mg/l	2
Legend:	4. US EPA, Ed		e ECHA Registered Substances - Ecotoxicolo Oata 5. ECETOC Aquatic Hazard Assessment I		

## **DO NOT** discharge into sewer or waterways.

## Persistence and degradability

Ingredient	Persistence: Water/Soil	Persistence: Air
titanium dioxide	HIGH	HIGH

## Bioaccumulative potential

Ingredient	Bioaccumulation
titanium dioxide	LOW (BCF = 10)

## Mobility in soil

Ingredient	Mobility
titanium dioxide	LOW (Log KOC = 23.74)

#### Lubrication Engineers LE 452 ALMASOL Chain & Cable Medium

Issue Date: 23/12/2022 Print Date: 29/10/2024

#### **SECTION 13 Disposal considerations**

#### Waste treatment methods

Legislation addressing waste disposal requirements may differ by country, state and/ or territory. Each user must refer to laws operating in their area. In some areas, certain wastes must be tracked.

A Hierarchy of Controls seems to be common - the user should investigate:

- ▶ Reduction
- Reuse
- Recycling
- Disposal (if all else fails)

## Product / Packaging disposal

This material may be recycled if unused, or if it has not been contaminated so as to make it unsuitable for its intended use.

- ▶ DO NOT allow wash water from cleaning or process equipment to enter drains.
- It may be necessary to collect all wash water for treatment before disposal.
- ▶ In all cases disposal to sewer may be subject to local laws and regulations and these should be considered first.
- Where in doubt contact the responsible authority.
- ▶ Recycle wherever possible or consult manufacturer for recycling options.
- ▶ Consult State Land Waste Authority for disposal.
- Bury or incinerate residue at an approved site.
- Recycle containers if possible, or dispose of in an authorised landfill.

Ensure that the hazardous substance is disposed in accordance with the Hazardous Substances (Disposal) Notice 2017

#### **Disposal Requirements**

Not applicable as substance/ material is non hazardous.

#### **SECTION 14 Transport information**

#### **Labels Required**

Marine Pollutant	NO
HAZCHEM	Not Applicable

Land transport (UN): NOT REGULATED FOR TRANSPORT OF DANGEROUS GOODS

Air transport (ICAO-IATA / DGR): NOT REGULATED FOR TRANSPORT OF DANGEROUS GOODS

Sea transport (IMDG-Code / GGVSee): NOT REGULATED FOR TRANSPORT OF DANGEROUS GOODS

14.7.1. Transport in bulk according to Annex II of MARPOL and the IBC code

Not Applicable

## 14.7.2. Transport in bulk in accordance with MARPOL Annex V and the IMSBC Code

Product name	Group
mica	Not Available
titanium dioxide	Not Available
ferric oxide	Not Available

## 14.7.3. Transport in bulk in accordance with the IGC Code

Product name	Ship Type
mica	Not Available
titanium dioxide	Not Available
ferric oxide	Not Available

#### **SECTION 15 Regulatory information**

#### Safety, health and environmental regulations / legislation specific for the substance or mixture

This substance is to be managed using the conditions specified in an applicable Group Standard

HSR Number	Group Standard
Not Applicable	Not Applicable

Chemwatch: **4743-55**Version No: **8.1** 

#### Lubrication Engineers LE 452 ALMASOL Chain & Cable Medium

Issue Date: 23/12/2022
Print Date: 29/10/2024

Please refer to Section 8 of the SDS for any applicable tolerable exposure limit or Section 12 for environmental exposure limit.

#### mica is found on the following regulatory lists

International WHO List of Proposed Occupational Exposure Limit (OEL) Values for Manufactured Nanomaterials (MNMS)

New Zealand Inventory of Chemicals (NZIoC)

New Zealand Workplace Exposure Standards (WES)

#### titanium dioxide is found on the following regulatory lists

Chemical Footprint Project - Chemicals of High Concern List

International Agency for Research on Cancer (IARC) - Agents Classified by the IARC Monographs

International Agency for Research on Cancer (IARC) - Agents Classified by the IARC Monographs - Group 2B: Possibly carcinogenic to humans

International WHO List of Proposed Occupational Exposure Limit (OEL) Values for Manufactured Nanomaterials (MNMS)

New Zealand Inventory of Chemicals (NZIoC)

New Zealand Workplace Exposure Standards (WES)

#### ferric oxide is found on the following regulatory lists

International Agency for Research on Cancer (IARC) - Agents Classified by the IARC Monographs - Not Classified as Carcinogenic

International WHO List of Proposed Occupational Exposure Limit (OEL) Values for Manufactured Nanomaterials (MNMS)

New Zealand Inventory of Chemicals (NZIoC)

New Zealand Workplace Exposure Standards (WES)

#### **Additional Regulatory Information**

Not Applicable

#### **Hazardous Substance Location**

Subject to the Health and Safety at Work (Hazardous Substances) Regulations 2017.

Hazard Class	Quantities
Not Applicable	Not Applicable

#### **Certified Handler**

Subject to Part 4 of the Health and Safety at Work (Hazardous Substances) Regulations 2017.

Class of substance	Quantities
Not Applicable	Not Applicable

Refer Group Standards for further information

## Maximum quantities of certain hazardous substances permitted on passenger service vehicles

Subject to Regulation 13.14 of the Health and Safety at Work (Hazardous Substances) Regulations 2017.

Hazard Class	Gas (aggregate water capacity in mL)	Liquid (L)	Solid (kg)	Maximum quantity per package for each classification
Not Applicable	Not Applicable	Not Applicable	Not Applicable	Not Applicable

#### **Tracking Requirements**

Not Applicable

## **National Inventory Status**

National Inventory	Status		
Australia - AIIC / Australia Non-Industrial Use	Yes		
Canada - DSL	Yes		
Canada - NDSL	No (mica; ferric oxide)		
China - IECSC	Yes		
Europe - EINEC / ELINCS / NLP	Yes		
Japan - ENCS	No (mica)		
Korea - KECI	Yes		
New Zealand - NZIoC	Yes		
Philippines - PICCS	Yes		
USA - TSCA	TSCA Inventory 'Active' substance(s) (titanium dioxide; ferric oxide); No (mica)		

Version No. 8.1

#### Lubrication Engineers LE 452 ALMASOL Chain & Cable Medium

Print Date: 29/10/2024

Issue Date: 23/12/2022

National Inventory	Status	
Taiwan - TCSI	Yes	
Mexico - INSQ	Yes	
Vietnam - NCI	Yes	
Russia - FBEPH	Yes	
Legend:	Yes = All CAS declared ingredients are on the inventory No = One or more of the CAS listed ingredients are not on the inventory. These ingredients may be exempt or will require registration.	

#### **SECTION 16 Other information**

Revision Date	23/12/2022
Initial Date	01/11/2009

#### **SDS Version Summary**

Version	Date of Update	Sections Updated	
7.1	01/11/2019	One-off system update. NOTE: This may or may not change the GHS classification	
8.1	23/12/2022	Classification review due to GHS Revision change.	

#### Other information

Classification of the preparation and its individual components has drawn on official and authoritative sources as well as independent review by the Chemwatch Classification committee using available literature references.

The SDS is a Hazard Communication tool and should be used to assist in the Risk Assessment. Many factors determine whether the reported Hazards are Risks in the workplace or other settings. Risks may be determined by reference to Exposures Scenarios. Scale of use, frequency of use and current or available engineering controls must be considered.

#### **Definitions and abbreviations**

- PC TWA: Permissible Concentration-Time Weighted Average
- PC STEL: Permissible Concentration-Short Term Exposure Limit
- ▶ IARC: International Agency for Research on Cancer
- ACGIH: American Conference of Governmental Industrial Hygienists
- ▶ STEL: Short Term Exposure Limit
- ► TEEL: Temporary Emergency Exposure Limit。
- ▶ IDLH: Immediately Dangerous to Life or Health Concentrations
- ▶ ES: Exposure Standard
- ▶ OSF: Odour Safety Factor
- NOAEL: No Observed Adverse Effect Level
- ▶ LOAEL: Lowest Observed Adverse Effect Level
- ▶ TLV: Threshold Limit Value
- ▶ LOD: Limit Of Detection
- ▶ OTV: Odour Threshold Value
- ▶ BCF: BioConcentration Factors
- ▶ BEI: Biological Exposure Index
- ▶ DNEL: Derived No-Effect Level
- ▶ PNEC: Predicted no-effect concentration
- ▶ AIIC: Australian Inventory of Industrial Chemicals
- DSL: Domestic Substances List
- ▶ NDSL: Non-Domestic Substances List
- ▶ IECSC: Inventory of Existing Chemical Substance in China
- ▶ EINECS: European INventory of Existing Commercial chemical Substances
- ▶ ELINCS: European List of Notified Chemical Substances
- NLP: No-Longer Polymers
- ▶ ENCS: Existing and New Chemical Substances Inventory
- ▶ KECI: Korea Existing Chemicals Inventory
- NZIoC: New Zealand Inventory of Chemicals
- ▶ PICCS: Philippine Inventory of Chemicals and Chemical Substances
- TSCA: Toxic Substances Control Act
- ▶ TCSI: Taiwan Chemical Substance Inventory
- ▶ INSQ: Inventario Nacional de Sustancias Químicas
- NCI: National Chemical Inventory
- ▶ FBEPH: Russian Register of Potentially Hazardous Chemical and Biological Substances

#### This document is copyright.

Apart from any fair dealing for the purposes of private study, research, review or criticism, as permitted under the Copyright Act, no part may be reproduced by any process without written permission from CHEMWATCH.

Chemwatch: **4743-55**Version No: **8.1** 

Page **11** of **11** 

Lubrication Engineers LE 452 ALMASOL Chain & Cable Medium

Issue Date: 23/12/2022 Print Date: 29/10/2024

TEL (+61 3) 9572 4700.