

# **LE4700 MONOLEC Industrial Lubricant**

# **Lubrication Engineers NZ Ltd**

Chemwatch: 22-6150 Version No: 8.1

Safety Data Sheet according to the Health and Safety at Work (Hazardous Substances) Regulations 2017

Chemwatch Hazard Alert Code:

Issue Date: 23/12/2022 Print Date: 29/10/2024 S.GHS.NZL.EN

# SECTION 1 Identification of the substance / mixture and of the company / undertaking

#### **Product Identifier**

Product name	LE4700 MONOLEC Industrial Lubricant
Chemical Name	Not Applicable
Synonyms	Not Available
Chemical formula	Not Applicable
Other means of identification	Not Available

# Relevant identified uses of the substance or mixture and uses advised against

Relevant identified uses	Lubricant.
	Use according to manufacturer's directions.

#### Details of the manufacturer or supplier of the safety data sheet

Registered company name	Lubrication Engineers NZ Ltd
Address	11F Piermark Drive North Harbour Industrial Estate Albany, Auckland New Zealand
Telephone	+64 09 415 9411
Fax	+64 09 4158411
Website	Not Available
Email	Not Available

# **Emergency telephone number**

Association / Organisation	Lubrication Engineers NZ Ltd	CHEMWATCH EMERGENCY RESPONSE (24/7)		
Emergency telephone number(s)	+64 21 3385487	+64 800 700 112		
Other emergency telephone number(s)	Not Available	+61 3 9573 3188		

Once connected and if the message is not in your preferred language then please dial 01

#### **SECTION 2 Hazards identification**

#### Classification of the substance or mixture

Considered a Hazardous Substance according to the criteria of the New Zealand Hazardous Substances New Organisms legislation. Not regulated for transport of Dangerous Goods.

#### Chemwatch Hazard Ratings

		Min	Max	
Flammability	1			
Toxicity	1			
Body Contact	1			0 = Minimum 1 = Low
Reactivity	1			2 = Moderate
Chronic	0			3 = High 4 = Extreme

Classification <sup>[1]</sup>	Hazardous to the Aquatic Environment Long-Term Hazard Category 2
Legend:	1. Classified by Chemwatch; 2. Classification drawn from CCID EPA NZ; 3. Classification drawn from Regulation (EU) No 1272/2008 - Annex VI

Chemwatch: 22-6150 Version No: 8.1

Page 2 of 11

**LE4700 MONOLEC Industrial Lubricant** 

Issue Date: 23/12/2022 Print Date: 29/10/2024

**Determined by Chemwatch** using GHS/HSNO criteria

9.1B

#### Label elements

Hazard pictogram(s)



Signal word

**Not Applicable** 

#### Hazard statement(s)

H411

Toxic to aquatic life with long lasting effects.

#### Precautionary statement(s) Prevention

P273

Avoid release to the environment.

#### Precautionary statement(s) Response

P391

Collect spillage.

# Precautionary statement(s) Storage

Not Applicable

#### Precautionary statement(s) Disposal

P501

Dispose of contents/container to authorised hazardous or special waste collection point in accordance with any local regulation.

# **SECTION 3 Composition / information on ingredients**

#### **Substances**

See section below for composition of Mixtures

#### **Mixtures**

CAS No	%[weight]	Name		
8042-47-5	NotSpec	white mineral oil (petroleum)		
15890-25-2	1-5	1-5 <u>antimony diamyldithiocarbamate</u>		
Not Available	balance	Ingredients determined not to be hazardous		
Legend: 1. Classified by Chemwatch; 2. Classification drawn from CCID EPA NZ; 3. Classification drawn from Regulation (EU) No 1272/2008 - Annex VI; 4. Classification drawn from C&L * EU IOELVs available				

# **SECTION 4 First aid measures**

Description of first aid me	asures
Eye Contact	If this product comes in contact with the eyes:  • Wash out immediately with fresh running water.  • Ensure complete irrigation of the eye by keeping eyelids apart and away from eye and moving the eyelids by occasionally lifting the upper and lower lids.  • Seek medical attention without delay; if pain persists or recurs seek medical attention.  • Removal of contact lenses after an eye injury should only be undertaken by skilled personnel.
Skin Contact	If skin contact occurs:  Immediately remove all contaminated clothing, including footwear.  Flush skin and hair with running water (and soap if available).  Seek medical attention in event of irritation.
Inhalation	<ul> <li>If fumes, aerosols or combustion products are inhaled remove from contaminated area.</li> <li>Other measures are usually unnecessary.</li> </ul>
Ingestion	<ul> <li>If swallowed do NOT induce vomiting.</li> <li>If vomiting occurs, lean patient forward or place on left side (head-down position, if possible) to maintain open airway and prevent aspiration.</li> <li>Observe the patient carefully.</li> <li>Never give liquid to a person showing signs of being sleepy or with reduced awareness; i.e. becoming unconscious.</li> <li>Give water to rinse out mouth, then provide liquid slowly and as much as casualty can comfortably drink.</li> </ul>

Chemwatch: **22-6150** Page **3** of **11** 

Version No: 8.1 LE4700 MONOLEC Industrial Lubricant

Issue Date: 23/12/2022 Print Date: 29/10/2024

Seek medical advice.

#### Indication of any immediate medical attention and special treatment needed

Treat symptomatically.

- Heavy and persistent skin contamination over many years may lead to dysplastic changes. Pre-existing skin disorders may be aggravated by exposure to this product.
- In general, emesis induction is unnecessary with high viscosity, low volatility products, i.e. most oils and greases.
- High pressure accidental injection through the skin should be assessed for possible incision, irrigation and/or debridement.

**NOTE:** Injuries may not seem serious at first, but within a few hours tissue may become swollen, discoloured and extremely painful with extensive subcutaneous necrosis. Product may be forced through considerable distances along tissue planes.

#### **SECTION 5 Firefighting measures**

#### Extinguishing media

- Alcohol stable foam.
- Dry chemical powder.
- ▶ BCF (where regulations permit).
- Carbon dioxide.

Do not use a water jet to fight fire.

#### Special hazards arising from the substrate or mixture

Fire Incompat	bility
---------------	--------

Avoid contamination with oxidising agents i.e. nitrates, oxidising acids, chlorine bleaches, pool chlorine etc. as ignition may
result

#### Advice for firefighters

Fire Fighting	<ul> <li>Alert Fire Brigade and tell them location and nature of hazard.</li> <li>Wear breathing apparatus plus protective gloves.</li> <li>Prevent, by any means available, spillage from entering drains or water courses.</li> <li>Use water delivered as a fine spray to control fire and cool adjacent area.</li> </ul>
Fire/Explosion Hazard	<ul> <li>Combustible.</li> <li>Slight fire hazard when exposed to heat or flame.</li> <li>Heating may cause expansion or decomposition leading to violent rupture of containers.</li> <li>On combustion, may emit toxic fumes of carbon monoxide (CO).</li> <li>Combustion products include:         <ul> <li>carbon dioxide (CO2)</li> <li>sulfur oxides (SOx)</li> <li>metal oxides</li> <li>other pyrolysis products typical of burning organic material.</li> <li>May emit poisonous fumes.</li> <li>CARE: Water in contact with hot liquid may cause foaming and a steam explosion with wide scattering of hot oil and possible severe burns. Foaming may cause overflow of containers and may result in possible fire.</li> </ul> </li> </ul>

# **SECTION 6 Accidental release measures**

# Personal precautions, protective equipment and emergency procedures

See section 8

#### **Environmental precautions**

See section 12

### Methods and material for containment and cleaning up

Minor Spills	<ul> <li>Clean up all spills immediately.</li> <li>Avoid breathing vapours/ aerosols/ or dusts and avoid contact with skin and eyes.</li> <li>Control personal contact with the substance, by using protective equipment.</li> <li>Contain and absorb spill with sand, earth, inert material or vermiculite.</li> </ul>
Major Spills	<ul> <li>Clear area of personnel and move upwind.</li> <li>Alert Fire Brigade and tell them location and nature of hazard.</li> <li>Wear breathing apparatus plus protective gloves.</li> <li>Prevent, by any means available, spillage from entering drains or water course.</li> </ul>

Personal Protective Equipment advice is contained in Section 8 of the SDS.

# **SECTION 7 Handling and storage**

#### Precautions for safe handling

Safe handling

• Avoid all personal contact, including inhalation.

Chemwatch: 22-6150 Page 4 of 11

#### **LE4700 MONOLEC Industrial Lubricant**

Issue Date: 23/12/2022 Print Date: 29/10/2024

▶ Wear protective clothing when risk of exposure occurs. Use in a well-ventilated area. Prevent concentration in hollows and sumps. Store in original containers.

Other information

- Keep containers securely sealed.
- No smoking, naked lights or ignition sources.
- ▶ Store in a cool, dry, well-ventilated area.

#### Conditions for safe storage, including any incompatibilities

Suitable container

- ▶ Polyethylene or polypropylene container.
- Packing as recommended by manufacturer.
- Check all containers are clearly labelled and free from leaks.

Storage incompatibility

- Avoid strong acids, bases.
- Avoid reaction with oxidising agents



Version No: 8.1













- Must not be stored together

- May be stored together with specific preventions

- May be stored together

Note: Depending on other risk factors, compatibility assessment based on the table above may not be relevant to storage situations, particularly where large volumes of dangerous goods are stored and handled. Reference should be made to the Safety Data Sheets for each substance or article and risks assessed accordingly.

#### **SECTION 8 Exposure controls / personal protection**

#### **Control parameters**

#### Occupational Exposure Limits (OEL)

#### INGREDIENT DATA

Source	Ingredient	Material name	TWA	STEL	Peak	Notes
New Zealand Workplace Exposure Standards (WES)	white mineral oil (petroleum)	Oil mist, mineral	5 mg/m3	10 mg/m3	Not Available	(om) - Sampled by a method that does not collect vapour
New Zealand Workplace Exposure Standards (WES)	antimony diamyldithiocarbamate	Antimony and compounds, as Sb	0.5 mg/m3	Not Available	Not Available	Not Available

Ingredient	Original IDLH	Revised IDLH
white mineral oil (petroleum)	2,500 mg/m3	Not Available
antimony diamyldithiocarbamate	50 mg/m3	Not Available

### **Exposure controls**

#### Appropriate engineering controls

Engineering controls are used to remove a hazard or place a barrier between the worker and the hazard. Well-designed engineering controls can be highly effective in protecting workers and will typically be independent of worker interactions to provide this high level of protection.

The basic types of engineering controls are:

Process controls which involve changing the way a job activity or process is done to reduce the risk.

Enclosure and/or isolation of emission source which keeps a selected hazard "physically" away from the worker and ventilation that strategically "adds" and "removes" air in the work environment.

Individual protection measures, such as personal protective equipment









# Eye and face protection

- Safety glasses with side shields.
- ► Chemical goggles. [AS/NZS 1337.1, EN166 or national equivalent]
- Contact lenses may pose a special hazard; soft contact lenses may absorb and concentrate irritants. A written policy document, describing the wearing of lenses or restrictions on use, should be created for each workplace or task.

# Skin protection

#### See Hand protection below

# Hands/feet protection

- Wear chemical protective gloves, e.g. PVC.
- Wear safety footwear or safety gumboots, e.g. Rubber

# **Body protection**

#### See Other protection below

- Other protection
- ▶ Overalls

LE4700 MONOLEC Industrial Lubricant

Issue Date: **23/12/2022**Print Date: **29/10/2024** 

- ▶ P.V.C apron.
- Barrier cream.
- Skin cleansing cream.

#### Respiratory protection

Version No: 8.1

Type A-P Filter of sufficient capacity. (AS/NZS 1716 & 1715, EN 143:2000 & 149:2001, ANSI Z88 or national equivalent)

**Appearance** Red paste with a hydrocarbon-like odour; not miscible with water.

Where the concentration of gas/particulates in the breathing zone, approaches or exceeds the "Exposure Standard" (or ES), respiratory protection is required. Degree of protection varies with both face-piece and Class of filter; the nature of protection varies with Type of filter.

Required Minimum Protection Factor	Half-Face Respirator	Full-Face Respirator	Powered Air Respirator
up to 10 x ES	A-AUS P2	-	A-PAPR-AUS / Class 1 P2
up to 50 x ES	-	A-AUS / Class 1 P2	-
up to 100 x ES	-	A-2 P2	A-PAPR-2 P2 ^

<sup>^ -</sup> Full-face

A(All classes) = Organic vapours, B AUS or B1 = Acid gasses, B2 = Acid gas or hydrogen cyanide(HCN), B3 = Acid gas or hydrogen cyanide(HCN), E = Sulfur dioxide(SO2), G = Agricultural chemicals, K = Ammonia(NH3), Hg = Mercury, NO = Oxides of nitrogen, MB = Methyl bromide, AX = Low boiling point organic compounds(below 65 degC)

# **SECTION 9 Physical and chemical properties**

# Information on basic physical and chemical properties

Physical state	Non Slump Paste	Relative density (Water = 1)	0.95
Odour	Not Available	Partition coefficient n- octanol / water	Not Available
Odour threshold	Not Available	Auto-ignition temperature (°C)	Not Available
pH (as supplied)	6-8	Decomposition temperature (°C)	Not Available
Melting point / freezing point (°C)	Not Available	Viscosity (cSt)	Not Available
Initial boiling point and boiling range (°C)	Not Available	Molecular weight (g/mol)	Not Applicable
Flash point (°C)	260	Taste	Not Available
Evaporation rate	Not Available	Explosive properties	Not Available
Flammability	Not Applicable	Oxidising properties	Not Available
Upper Explosive Limit (%)	Not Available	Surface Tension (dyn/cm or mN/m)	Not Available
Lower Explosive Limit (%)	Not Available	Volatile Component (%vol)	Not Available
Vapour pressure (kPa)	Not Available	Gas group	Not Available
Solubility in water	Immiscible	pH as a solution (1%)	Not Available
Vapour density (Air = 1)	<1	VOC g/L	Not Available
Heat of Combustion (kJ/g)	Not Available	Ignition Distance (cm)	Not Available
Flame Height (cm)	Not Available	Flame Duration (s)	Not Available
Enclosed Space Ignition Time Equivalent (s/m3)	Not Available	Enclosed Space Ignition Deflagration Density (g/m3)	Not Available

# **SECTION 10 Stability and reactivity**

Reactivity	See section 7
Chemical stability	Product is considered stable and hazardous polymerisation will not occur.
Possibility of hazardous reactions	See section 7
Conditions to avoid	See section 7
Incompatible materials	See section 7
Hazardous decomposition products	See section 5

Version No. 8.1

**LE4700 MONOLEC Industrial Lubricant** 

Issue Date: 23/12/2022 Print Date: 29/10/2024

# **SECTION 11 Toxicological information**

Information	on	toxico	logical	effects
-------------	----	--------	---------	---------

oraor. or. toxoo.og.o	
Inhaled	There is some evidence to suggest that the material can cause respiratory irritation in some persons. The body's response to such irritation can cause further lung damage.  Inhalation hazard is increased at higher temperatures.  Inhalation of oil droplets or aerosols may cause discomfort and may produce chemical inflammation of the lungs.
Ingestion	Accidental ingestion of the material may be damaging to the health of the individual.
Skin Contact	There is some evidence to suggest that this material can cause inflammation of the skin on contact in some persons.  Open cuts, abraded or irritated skin should not be exposed to this material  The material may accentuate any pre-existing dermatitis condition
Eye	There is some evidence to suggest that this material can cause eye irritation and damage in some persons.
Chronic	Substance accumulation, in the human body, may occur and may cause some concern following repeated or long-term occupational exposure.  Oil may contact the skin or be inhaled. Extended exposure can lead to eczema, inflammation of hair follicles, pigmentation of the face and warts on the soles of the feet.

<b>LE4700 MONOLEC</b>	TOXICITY	IRRITATION	
Industrial Lubricant	Not Available	Not Available	
	TOXICITY	IRRITATION	
white mineral oil	Dermal (rabbit) LD50: >2000 mg/kg <sup>[1]</sup>	Eye: no adverse effect observed (not irritating) <sup>[1]</sup>	
(petroleum)	Inhalation (Rat) LC50: >4.5 mg/l4h <sup>[1]</sup>	Skin: no adverse effect observed (not irritating) <sup>[1]</sup>	
	Oral (Rat) LD50: >5000 mg/kg <sup>[2]</sup>		
	TOXICITY	IRRITATION	
antimony diamyldithiocarbamate	Dermal (rabbit) LD50: >16000 mg/kg <sup>[2]</sup>	Eye: no adverse effect observed (not irritating) <sup>[1]</sup>	
	Oral (Rat) LD50: >16400 mg/kg <sup>[2]</sup>	Skin: no adverse effect observed (not irritating) <sup>[1]</sup>	

Legend

 Value obtained from Europe ECHA Registered Substances - Acute toxicity 2. Value obtained from manufacturer's SDS. Unless otherwise specified data extracted from RTECS - Register of Toxic Effect of chemical Substances

Oral (rat) TCLo: 92000 mg/kg/92D-Cont. Generally the toxicity and irritation is of low order. White oils and highly/solvent refined oils have not shown the long term risk of skin cancer that follows persistent skin contamination with some other mineral oils, due in all probability to refining that produces low content of both polyaromatics (PAH) and benz-alpha-pyrenes (BaP) The substance is classified by IARC as Group 3:

 $\ensuremath{\text{NOT}}$  classifiable as to its carcinogenicity to humans.

Evidence of carcinogenicity may be inadequate or limited in animal testing.

For highly and severely refined distillate base oils:

In animal studies, the acute, oral, semilethal dose is >5g/kg body weight and the semilethal dose by skin contact is >2g/kg body weight. The semilethal concentration for inhalation is 2.18 to >4 mg/L. The materials have varied from "non-irritating" to "moderately irritating" when tested for skin and eye irritation. Testing for sensitisation has been negative.

The materials included in the Lubricating Base Oils category are related from both process and physical-chemical perspectives; The potential toxicity of a specific distillate base oil is inversely related to the severity or extent of processing the oil has undergone, since:

- The adverse effects of these materials are associated with undesirable components, and
- The levels of the undesirable components are inversely related to the degree of processing;
- Distillate base oils receiving the same degree or extent of processing will have similar toxicities;
- The potential toxicity of residual base oils is independent of the degree of processing the oil receives.
- The reproductive and developmental toxicity of the distillate base oils is inversely related to the degree of processing. Unrefined & mildly refined distillate base oils contain the highest levels of undesirable components, have the largest variation of hydrocarbon molecules and have shown the highest potential cancer-causing and mutation-causing activities. Highly and severely refined distillate base oils are produced from unrefined and mildly refined oils by removing or transforming undesirable components. In comparison to unrefined and mildly refined base oils, the highly and severely refined distillate base oils have a smaller range of hydrocarbon molecules and have demonstrated very low mammalian toxicity. Testing of residual oils for mutation-causing and cancer-causing potential has shown negative results, supporting the belief that these materials lack biologically active components or the components are largely non-bioavailable due to their molecular size.

  Toxicity testing has consistently shown that lubricating base oils have low acute toxicities.

# ANTIMONY DIAMYLDITHIOCARBAMATE

WHITE MINERAL OIL

(PETROLEUM)

No significant acute toxicological data identified in literature search.

Acute Toxicity	×	Carcinogenicity	×
Skin Irritation/Corrosion	×	Reproductivity	×
Serious Eye Damage/Irritation	×	STOT - Single Exposure	×

Chemwatch: 22-6150 Page 7 of 11

**LE4700 MONOLEC Industrial Lubricant** 

Issue Date: 23/12/2022 Print Date: 29/10/2024

Respiratory or Skin sensitisation	×	STOT - Repeated Exposure	×
Mutagenicity	×	Aspiration Hazard	×

X - Data either not available or does not fill the criteria for classification Legend: Data available to make classification

#### **SECTION 12 Ecological information**

#### Toxicity

Version No: 8.1

LE4700 MONOLEC Industrial Lubricant	Endpoint	Test Duration (hr)	Species	Value	Source
	Not Available	Not Available	Not Available	Not Available	Not Available
white mineral oil	Endpoint	Test Duration (hr)	Species	Value	Source
(petroleum)	LC50	96h	Fish	>10000mg/L	2
antimony	Endpoint	Test Duration (hr)	Species	Value	Source
antimony diamyldithiocarbamate	Not Available	Not Available	Not Available	Not Available	Not Available
Legend:	Extracted from 1. IUCLID Toxicity Data 2. Europe ECHA Registered Substances - Ecotoxicological Information - Aquatic Toxicity 4. US EPA, Ecotox database - Aquatic Toxicity Data 5. ECETOC Aquatic Hazard Assessment Data 6. NITE (Japan) - Bioconcentration Data 7. METI (Japan) - Bioconcentration Data 8. Vendor Data				

DO NOT discharge into sewer or waterways.

#### Persistence and degradability

Ingredient	Persistence: Water/Soil	Persistence: Air
	No Data available for all ingredients	No Data available for all ingredients

### Bioaccumulative potential

Ingredient	Bioaccumulation
	No Data available for all ingredients

#### Mobility in soil

Ingredient	Mobility	
	No Data available for all ingredients	

#### **SECTION 13 Disposal considerations**

disposal

#### Waste treatment methods

Product / Packaging

- ▶ DO NOT allow wash water from cleaning or process equipment to enter drains.
- It may be necessary to collect all wash water for treatment before disposal.
- ▶ In all cases disposal to sewer may be subject to local laws and regulations and these should be considered first.
- Where in doubt contact the responsible authority.
- Recycle wherever possible or consult manufacturer for recycling options.
- Consult State Land Waste Authority for disposal.
- Bury or incinerate residue at an approved site.
- ▶ Recycle containers if possible, or dispose of in an authorised landfill.

Ensure that the hazardous substance is disposed in accordance with the Hazardous Substances (Disposal) Notice 2017

#### **Disposal Requirements**

Packages that have been in direct contact with the hazardous substance must be only disposed if the hazardous substance was appropriately removed and cleaned out from the package. The package must be disposed according to the manufacturer's directions taking into account the material it is made of. Packages which hazardous content have been appropriately treated and removed may be recycled.

The hazardous substance must only be disposed if it has been treated by a method that changed the characteristics or composition of the substance and it is no longer hazardous.

#### **SECTION 14 Transport information**

LE4700 MONOLEC Industrial Lubricant

Issue Date: 23/12/2022 Print Date: 29/10/2024

# Labels Required



Land transport (UN): NOT REGULATED FOR TRANSPORT OF DANGEROUS GOODS

Air transport (ICAO-IATA / DGR): NOT REGULATED FOR TRANSPORT OF DANGEROUS GOODS

Sea transport (IMDG-Code / GGVSee): NOT REGULATED FOR TRANSPORT OF DANGEROUS GOODS

#### 14.7.1. Transport in bulk according to Annex II of MARPOL and the IBC code

Not Applicable

#### 14.7.2. Transport in bulk in accordance with MARPOL Annex V and the IMSBC Code

Product name	Group
white mineral oil (petroleum)	Not Available
antimony diamyldithiocarbamate	Not Available

#### 14.7.3. Transport in bulk in accordance with the IGC Code

Product name	Ship Type
white mineral oil (petroleum)	Not Available
antimony diamyldithiocarbamate	Not Available

# **SECTION 15 Regulatory information**

# Safety, health and environmental regulations / legislation specific for the substance or mixture

This substance is to be managed using the conditions specified in an applicable Group Standard

HSR Number	Group Standard		
HSR002521	Animal Nutritional and Animal Care Products Group Standard 2020		
HSR002530	Cleaning Products Subsidiary Hazard Group Standard 2020		
HSR002535	Gases under Pressure Mixtures Subsidiary Hazard Group Standard 2020		
HSR002503	Additives Process Chemicals and Raw Materials Subsidiary Hazard Group Standard 2020		
HSR002606	Lubricants Lubricant Additives Coolants and Anti freeze Agents Subsidiary Hazard Group Standard 2020		
HSR002612	Metal Industry Products Subsidiary Hazard Group Standard 2020		
HSR002624	N.O.S. Subsidiary Hazard Group Standard 2020		
HSR002638	Photographic Chemicals Subsidiary Hazard Group Standard 2020		
HSR002644	olymers Subsidiary Hazard Group Standard 2020		
HSR002647	Reagent Kits Group Standard 2020		
HSR002648	Refining Catalysts Group Standard 2020		
HSR002653	Solvents Subsidiary Hazard Group Standard 2020		
HSR002670	Surface Coatings and Colourants Subsidiary Hazard Group Standard 2020		
HSR002684	Water Treatment Chemicals Subsidiary Hazard Group Standard 2020		
HSR100425	Pharmaceutical Active Ingredients Group Standard 2020		
HSR002600	Leather and Textile Products Subsidiary Hazard Group Standard 2020		
HSR002544	Construction Products Subsidiary Hazard Group Standard 2020		
HSR002549	Corrosion Inhibitors Subsidiary Hazard Group Standard 2020		
HSR002552	Cosmetic Products Group Standard 2020		
HSR002558	Dental Products Subsidiary Hazard Group Standard 2020		
HSR002565	Embalming Products Subsidiary Hazard Group Standard 2020		
HSR002571	Fertilisers Subsidiary Hazard Group Standard 2020		
HSR002573	Fire Fighting Chemicals Group Standard 2021		

Version No: 8.1

#### **LE4700 MONOLEC Industrial Lubricant**

Issue Date: 23/12/2022 Print Date: 29/10/2024

HSR Number	Group Standard	
HSR002578	Food Additives and Fragrance Materials Subsidiary Hazard Group Standard 2020	
HSR002585	Fuel Additives Subsidiary Hazard Group Standard 2020	
HSR002596	Laboratory Chemicals and Reagent Kits Group Standard 2020	
HSR008053	Graphic Materials Group Standard 2020	
HSR100580	Tattoo and Permanent Makeup Substances Group Standard 2020	
HSR100757	Veterinary Medicines Limited Pack Size Finished Dose Group Standard 2020	
HSR100758	Veterinary Medicines Non dispersive Closed System Application Group Standard 2020	
HSR100759	Veterinary Medicines Non dispersive Open System Application Group Standard 2020	
HSR100592	Agricultural Compounds Special Circumstances Group Standard 2020	
HSR100756	Active Ingredients for Use in the Manufacture of Agricultural Compounds Group Standard 2020	

Please refer to Section 8 of the SDS for any applicable tolerable exposure limit or Section 12 for environmental exposure limit.

#### white mineral oil (petroleum) is found on the following regulatory lists

Chemical Footprint Project - Chemicals of High Concern List

International Agency for Research on Cancer (IARC) - Agents Classified by the IARC Monographs

International Agency for Research on Cancer (IARC) - Agents Classified by the IARC Monographs - Group 1: Carcinogenic to humans

International Agency for Research on Cancer (IARC) - Agents Classified by the IARC Monographs - Not Classified as Carcinogenic

New Zealand Approved Hazardous Substances with controls

New Zealand Hazardous Substances and New Organisms (HSNO) Act - Classification of Chemicals

New Zealand Inventory of Chemicals (NZIoC)

New Zealand Workplace Exposure Standards (WES)

#### antimony diamyldithiocarbamate is found on the following regulatory lists

New Zealand Inventory of Chemicals (NZIoC)

New Zealand Land Transport Rule: Dangerous Goods 2005 - Schedule 1 Quantity limits for dangerous goods

New Zealand Workplace Exposure Standards (WES)

#### **Additional Regulatory Information**

Not Applicable

# **Hazardous Substance Location**

Subject to the Health and Safety at Work (Hazardous Substances) Regulations 2017.

Hazard Class	Quantities
Not Applicable	Not Applicable

#### **Certified Handler**

Subject to Part 4 of the Health and Safety at Work (Hazardous Substances) Regulations 2017.

Class of substance	Quantities
Not Applicable	Not Applicable

Refer Group Standards for further information

#### Maximum quantities of certain hazardous substances permitted on passenger service vehicles

Subject to Regulation 13.14 of the Health and Safety at Work (Hazardous Substances) Regulations 2017.

Hazard Class	Gas (aggregate water capacity in mL)	Liquid (L)	Solid (kg)	Maximum quantity per package for each classification
Not Applicable	Not Applicable	Not Applicable	Not Applicable	Not Applicable

#### **Tracking Requirements**

Not Applicable

# **National Inventory Status**

•	
National Inventory	Status
Australia - AIIC / Australia Non-Industrial Use	Yes
Canada - DSL	Yes
Canada - NDSL	No (white mineral oil (petroleum); antimony diamyldithiocarbamate)

Page 10 of 11 Issue Date: 23/12/2022 Print Date: 29/10/2024 **LE4700 MONOLEC Industrial Lubricant** 

National Inventory	Status			
China - IECSC	Yes			
Europe - EINEC / ELINCS / NLP	Yes			
Japan - ENCS	/es			
Korea - KECI	Yes			
New Zealand - NZIoC	/es			
Philippines - PICCS	Yes			
USA - TSCA	All chemical substances in this product have been designated as TSCA Inventory 'Active'			
Taiwan - TCSI	Yes			
Mexico - INSQ	No (antimony diamyldithiocarbamate)			
Vietnam - NCI	Yes			
Russia - FBEPH	Yes			
Legend:	Yes = All CAS declared ingredients are on the inventory No = One or more of the CAS listed ingredients are not on the inventory. These ingredients may be exempt or will require registration.			

#### **SECTION 16 Other information**

Revision Date	23/12/2022
Initial Date	01/11/2009

#### **SDS Version Summary**

Version No. 8.1

Version	Date of Update	Sections Updated
7.1	01/11/2019	One-off system update. NOTE: This may or may not change the GHS classification
8.1	23/12/2022	Classification review due to GHS Revision change.

#### Other information

Classification of the preparation and its individual components has drawn on official and authoritative sources as well as independent review by the Chemwatch Classification committee using available literature references.

The SDS is a Hazard Communication tool and should be used to assist in the Risk Assessment. Many factors determine whether the reported Hazards are Risks in the workplace or other settings. Risks may be determined by reference to Exposures Scenarios. Scale of use, frequency of use and current or available engineering controls must be considered.

# **Definitions and abbreviations**

- ▶ PC TWA: Permissible Concentration-Time Weighted Average
- ▶ PC STEL: Permissible Concentration-Short Term Exposure Limit
- ▶ IARC: International Agency for Research on Cancer
- ▶ ACGIH: American Conference of Governmental Industrial Hygienists
- ▶ STEL: Short Term Exposure Limit
- ► TEEL: Temporary Emergency Exposure Limit。
- ▶ IDLH: Immediately Dangerous to Life or Health Concentrations
- ▶ ES: Exposure Standard
- ▶ OSF: Odour Safety Factor
- NOAEL: No Observed Adverse Effect Level
- LOAEL: Lowest Observed Adverse Effect Level
- ▶ TLV: Threshold Limit Value
- ▶ LOD: Limit Of Detection
- ▶ OTV: Odour Threshold Value
- ▶ BCF: BioConcentration Factors
- ▶ BEI: Biological Exposure Index
- ▶ DNEL: Derived No-Effect Level
- ▶ PNEC: Predicted no-effect concentration
- ▶ AIIC: Australian Inventory of Industrial Chemicals
- ▶ DSL: Domestic Substances List
- ▶ NDSL: Non-Domestic Substances List
- ▶ IECSC: Inventory of Existing Chemical Substance in China
- ▶ EINECS: European INventory of Existing Commercial chemical Substances
- ▶ ELINCS: European List of Notified Chemical Substances
- ▶ NLP: No-Longer Polymers
- ▶ ENCS: Existing and New Chemical Substances Inventory
- KECI: Korea Existing Chemicals Inventory
- ▶ NZIoC: New Zealand Inventory of Chemicals

Chemwatch: 22-6150 Page 11 of 11 Issue Date: 23/12/2022 Version No: 8.1 Print Date: 29/10/2024

#### **LE4700 MONOLEC Industrial Lubricant**

- ▶ PICCS: Philippine Inventory of Chemicals and Chemical Substances
- ► TSCA: Toxic Substances Control Act
- ▶ TCSI: Taiwan Chemical Substance Inventory
- ▶ INSQ: Inventario Nacional de Sustancias Químicas
- ▶ NCI: National Chemical Inventory
- ▶ FBEPH: Russian Register of Potentially Hazardous Chemical and Biological Substances

# This document is copyright.

Apart from any fair dealing for the purposes of private study, research, review or criticism, as permitted under the Copyright Act, no part may be reproduced by any process without written permission from CHEMWATCH.

TEL (+61 3) 9572 4700.