

LE4140 H1 QUINPLEX Food Grade Gear Lubricant

Lubrication Engineers NZ Ltd

Chemwatch: 22-6148 Version No: 9.1

Safety Data Sheet according to the Health and Safety at Work (Hazardous Substances) Regulations 2017

Chemwatch Hazard Alert Code: 2

Issue Date: 23/12/2022
Print Date: 29/10/2024
S.GHS.NZL.EN

SECTION 1 Identification of the substance / mixture and of the company / undertaking

Product Identifier

| Product name | E4140 H1 QUINPLEX Food Grade Gear Lubricant | |
|-------------------------------|---|--|
| Chemical Name | Not Applicable | |
| Synonyms | Not Available | |
| Chemical formula | Not Applicable | |
| Other means of identification | Not Available | |

Relevant identified uses of the substance or mixture and uses advised against

| Relevant identified uses | Lubricant. Use according to manufacturer's directions. |
|--------------------------|--|
| | |

Details of the manufacturer or supplier of the safety data sheet

| Registered company name | Lubrication Engineers NZ Ltd | | |
|-------------------------|---|--|--|
| Address | F Piermark Drive North Harbour Industrial Estate Albany, Auckland New Zealand | | |
| Telephone | 09 415 9411 | | |
| Fax | +64 09 4158411 | | |
| Website | Not Available | | |
| Email | Not Available | | |

Emergency telephone number

| Association / Organisation | Lubrication Engineers NZ Ltd | CHEMWATCH EMERGENCY RESPONSE (24/7) | | |
|-------------------------------------|------------------------------|-------------------------------------|--|--|
| Emergency telephone number(s) | +64 21 3385487 | +64 800 700 112 | | |
| Other emergency telephone number(s) | Not Available | +61 3 9573 3188 | | |

Once connected and if the message is not in your preferred language then please dial 01

SECTION 2 Hazards identification

Classification of the substance or mixture

Not considered a Hazardous Substance according to the criteria of the New Zealand Hazardous Substances New Organisms legislation. Not regulated for transport of Dangerous Goods.

Chemwatch Hazard Ratings

| | Min | Max | |
|--------------|-----|-----|-------------------------|
| Flammability | 1 | | |
| Toxicity | 1 | | |
| Body Contact | 2 | | 0 = Minimum 1 = Low |
| Reactivity | 1 | | 2 = Moderate |
| Chronic | 0 | | 3 = High 4 = Extreme |

| Classification ^[1] | Non hazardous |
|-------------------------------|---|
| Legend: | 1. Classified by Chemwatch; 2. Classification drawn from CCID EPA NZ; 3. Classification drawn from Regulation (EU) No 1272/2008 - Annex VI |

Chemwatch: 22-6148 Page 2 of 14

Version No: 9.1 LE4140 H1 QUINPLEX Food Grade Gear Lubricant

Issue Date: **23/12/2022**Print Date: **29/10/2024**

Determined by Chemwatch using GHS/HSNO criteria

Not Available

Label elements

Hazard pictogram(s)

Not Applicable

Signal word

Not Applicable

Hazard statement(s)

Not Applicable

Precautionary statement(s) Prevention

Not Applicable

Precautionary statement(s) Response

Not Applicable

Precautionary statement(s) Storage

Not Applicable

Precautionary statement(s) Disposal

Not Applicable

SECTION 3 Composition / information on ingredients

Substances

See section below for composition of Mixtures

Mixtures

| CAS No | %[weight] | Name | |
|---------------|---|---|--|
| 8042-47-5 | NotSpec | white mineral oil (petroleum) | |
| 64742-46-7. | 1-5 | distillates, petroleum, middle, hydrotreated | |
| 140-88-5 | NotSpec | ethyl acrylate | |
| 6683-19-8 | NotSpec | pentaerythritol tetrabutylhydroxyhydrocinnamate | |
| 65-85-0 | NotSpec | benzoic acid | |
| 103-11-7 | NotSpec | 2-ethylhexyl acrylate | |
| Not Available | balance | Ingredients determined not to be hazardous | |
| Legend: | Legend: 1. Classified by Chemwatch; 2. Classification drawn from CCID EPA NZ; 3. Classification drawn from Regulation (EU) No | | |

SECTION 4 First aid measures

Description of first aid measures

| Description of first aid me | asures |
|-----------------------------|---|
| Eye Contact | If this product comes in contact with the eyes: Wash out immediately with fresh running water. Ensure complete irrigation of the eye by keeping eyelids apart and away from eye and moving the eyelids by occasionally lifting the upper and lower lids. Seek medical attention without delay; if pain persists or recurs seek medical attention. Removal of contact lenses after an eye injury should only be undertaken by skilled personnel. |
| Skin Contact | If skin or hair contact occurs: ▶ Flush skin and hair with running water (and soap if available). ▶ Seek medical attention in event of irritation. |
| Inhalation | If fumes, aerosols or combustion products are inhaled remove from contaminated area. Other measures are usually unnecessary. |
| Ingestion | If swallowed do NOT induce vomiting. If vomiting occurs, lean patient forward or place on left side (head-down position, if possible) to maintain open airway and prevent aspiration. Observe the patient carefully. Never give liquid to a person showing signs of being sleepy or with reduced awareness; i.e. becoming unconscious. Give water to rinse out mouth, then provide liquid slowly and as much as casualty can comfortably drink. Seek medical advice. |

Chemwatch: 22-6148 Page 3 of 14 Issue Date: 23/12/2022

LE4140 H1 QUINPLEX Food Grade Gear Lubricant

Indication of any immediate medical attention and special treatment needed

Treat symptomatically.

Version No: 9.1

- Heavy and persistent skin contamination over many years may lead to dysplastic changes. Pre-existing skin disorders may be aggravated by exposure to this product.
- In general, emesis induction is unnecessary with high viscosity, low volatility products, i.e. most oils and greases.
- High pressure accidental injection through the skin should be assessed for possible incision, irrigation and/or debridement.

NOTE: Injuries may not seem serious at first, but within a few hours tissue may become swollen, discoloured and extremely painful with extensive subcutaneous necrosis. Product may be forced through considerable distances along tissue planes.

SECTION 5 Firefighting measures

Extinguishing media

- Alcohol stable foam.
- Dry chemical powder.
- BCF (where regulations permit).
- Carbon dioxide.

Do not use a water jet to fight fire.

Special hazards arising from the substrate or mixture

Fire Incompatibility

Avoid contamination with oxidising agents i.e. nitrates, oxidising acids, chlorine bleaches, pool chlorine etc. as ignition may
result

Advice for firefighters

| Advice for intelligities | | | | |
|--------------------------|--|--|--|--|
| Fire Fighting | Alert Fire Brigade and tell them location and nature of hazard. Wear full body protective clothing with breathing apparatus. Prevent, by any means available, spillage from entering drains or water course. Use water delivered as a fine spray to control fire and cool adjacent area. | | | |
| Fire/Explosion Hazard | Combustible. Slight fire hazard when exposed to heat or flame. Heating may cause expansion or decomposition leading to violent rupture of containers. On combustion, may emit toxic fumes of carbon monoxide (CO). Combustion products include: carbon dioxide (CO2) other pyrolysis products typical of burning organic material. May emit poisonous fumes. CARE: Water in contact with hot liquid may cause foaming and a steam explosion with wide scattering of hot oil and possible severe burns. Foaming may cause overflow of containers and may result in possible fire. | | | |

SECTION 6 Accidental release measures

Personal precautions, protective equipment and emergency procedures

See section 8

Environmental precautions

See section 12

Methods and material for containment and cleaning up

| Minor Spills | Slippery when spilt. Remove all ignition sources. Clean up all spills immediately. Avoid breathing vapours and contact with skin and eyes. Control personal contact with the substance, by using protective equipment. |
|--------------|--|
| Major Spills | Slippery when spilt. Moderate hazard. Clear area of personnel and move upwind. Alert Fire Brigade and tell them location and nature of hazard. Wear breathing apparatus plus protective gloves. |

Personal Protective Equipment advice is contained in Section 8 of the SDS

SECTION 7 Handling and storage

Precautions for safe handling

Safe handling

- ► Avoid all personal contact, including inhalation.
- Wear protective clothing when risk of exposure occurs.
- ▶ Use in a well-ventilated area.

Print Date: 29/10/2024

Chemwatch: **22-6148** Page **4** of **14**

Version No: 9.1

LE4140 H1 QUINPLEX Food Grade Gear Lubricant

Issue Date: 23/12/2022
Print Date: 29/10/2024

Other information

- Prevent concentration in hollows and sumps.
- Store in original containers.
- ▶ Keep containers securely sealed.
- ▶ No smoking, naked lights or ignition sources.
- ▶ Store in a cool, dry, well-ventilated area.

Conditions for safe storage, including any incompatibilities

Suitable container

- ▶ Metal can or drum
- ▶ Packaging as recommended by manufacturer.
- ▶ Check all containers are clearly labelled and free from leaks.

Storage incompatibility

- Avoid strong acids, bases.
- ► Avoid reaction with oxidising agents















X — Must not be stored together

May be stored together with specific preventions

May be stored together

Note: Depending on other risk factors, compatibility assessment based on the table above may not be relevant to storage situations, particularly where large volumes of dangerous goods are stored and handled. Reference should be made to the Safety Data Sheets for each substance or article and risks assessed accordingly.

SECTION 8 Exposure controls / personal protection

Control parameters

Occupational Exposure Limits (OEL)

INGREDIENT DATA

| Source | Ingredient | Material name | TWA | STEL | Peak | Notes |
|---|---|--|----------------------|-----------------------|------------------|---|
| New Zealand Workplace Exposure Standards (WES) | white mineral oil (petroleum) | Oil mist, mineral | 5 mg/m3 | 10 mg/m3 | Not Available | (om) - Sampled by a method that does not collect vapour |
| New Zealand Workplace Exposure Standards (WES) | distillates, petroleum, middle, hydrotreated | Oil mist, mineral | 5 mg/m3 | 10 mg/m3 | Not Available | (om) - Sampled by a method that does not collect vapour |
| New Zealand Workplace Exposure Standards (WES) | ethyl acrylate | Ethyl acrylate | 2 ppm / 8.3 mg/m3 | 16.6 mg/m3 / 4 ppm | Not Available | (dsen) - Dermal sensitiser (skin) - Skin absorption |
| New Zealand Workplace Exposure Standards (WES) | benzoic acid | Respirable dust (not otherwise classified) | 3 mg/m3 | Not Available | Not Available | Not Available |
| New Zealand Workplace Exposure Standards (WES) | benzoic acid | Inhalable dust (not otherwise classified) | 10 mg/m3 | Not Available | Not Available | Not Available |

| Ingredient | Original IDLH | Revised IDLH |
|--|---------------|---------------|
| white mineral oil (petroleum) | 2,500 mg/m3 | Not Available |
| distillates, petroleum, middle, hydrotreated | 2,500 mg/m3 | Not Available |
| ethyl acrylate | 300 ppm | Not Available |
| pentaerythritol tetrabutylhydroxyhydrocinnamate | Not Available | Not Available |
| benzoic acid | Not Available | Not Available |
| 2-ethylhexyl acrylate | Not Available | Not Available |

Occupational Exposure Banding

| Ingredient | Occupational Exposure Band Rating | Occupational Exposure Band Limit |
|-----------------------|---|---|
| 2-ethylhexyl acrylate | E ≤ 0.1 ppm | |
| Notes: | Occupational exposure banding is a process of assigning chemical potency and the adverse health outcomes associated with exposure band (OEB), which corresponds to a range of exposure concentration. | ure. The output of this process is an occupational exposure |

Exposure controls

Chemwatch: 22-6148 Page 5 of 14

Issue Date: 23/12/2022 Version No. 9.1 Print Date: 29/10/2024

LE4140 H1 QUINPLEX Food Grade Gear Lubricant

Engineering controls are used to remove a hazard or place a barrier between the worker and the hazard. Well-designed engineering controls can be highly effective in protecting workers and will typically be independent of worker interactions to provide this high level of protection. Appropriate engineering The basic types of engineering controls are: controls Process controls which involve changing the way a job activity or process is done to reduce the risk. Enclosure and/or isolation of emission source which keeps a selected hazard "physically" away from the worker and ventilation that strategically "adds" and "removes" air in the work environment. Individual protection measures, such as personal protective equipment Safety glasses with side shields. ► Chemical goggles. [AS/NZS 1337.1, EN166 or national equivalent] Eye and face protection Contact lenses may pose a special hazard; soft contact lenses may absorb and concentrate irritants. A written policy document, describing the wearing of lenses or restrictions on use, should be created for each workplace or task. Skin protection The selection of suitable gloves does not only depend on the material, but also on further marks of quality which vary from

Hands/feet protection

manufacturer to manufacturer. Where the chemical is a preparation of several substances, the resistance of the glove material can not be calculated in advance and has therefore to be checked prior to the application. The exact break through time for substances has to be obtained from the manufacturer of the protective gloves and has to be

observed when making a final choice. Personal hygiene is a key element of effective hand care.

- Wear chemical protective gloves, e.g. PVC
- ▶ Wear safety footwear or safety gumboots, e.g. Rubber

Body protection

See Other protection below

Other protection

- Overalls
- P.V.C apron.
- Barrier cream.
- ▶ Skin cleansing cream.

Recommended material(s)

GLOVE SELECTION INDEX

Glove selection is based on a modified presentation of the:

"Forsberg Clothing Performance Index".

The effect(s) of the following substance(s) are taken into account in the computer-generated selection:

LE4140 H1 QUINPLEX Food Grade Gear Lubricant

| Material | СРІ |
|----------------|-----|
| BUTYL | А |
| PVA | А |
| TEFLON | Α |
| BUTYL/NEOPRENE | С |
| VITON/NEOPRENE | С |

^{*} CPI - Chemwatch Performance Index

A: Best Selection

B: Satisfactory; may degrade after 4 hours continuous immersion

C: Poor to Dangerous Choice for other than short term immersion

NOTE: As a series of factors will influence the actual performance of the glove, a final selection must be based on detailed observation. -

* Where the glove is to be used on a short term, casual or infrequent basis, factors such as "feel" or convenience (e.g. disposability), may dictate a choice of gloves which might otherwise be unsuitable following long-term or frequent use. A qualified practitioner should be consulted.

Respiratory protection

Type A-P Filter of sufficient capacity. (AS/NZS 1716 & 1715, EN 143:2000 & 149:2001, ANSI Z88 or national equivalent)

Where the concentration of gas/particulates in the breathing zone, approaches or exceeds the "Exposure Standard" (or ES), respiratory protection is required. Degree of protection varies with both face-piece and Class of filter; the nature of protection varies with Type of filter.

| Required Minimum Protection Factor | Half-Face Respirator | Full-Face Respirator | Powered Air Respirator |
|---------------------------------------|-------------------------|-------------------------|----------------------------|
| up to 10 x ES | A-AUS P2 | - | A-PAPR-AUS / Class 1 P2 |
| up to 50 x ES | - | A-AUS / Class 1 P2 | - |
| up to 100 x ES | - | A-2 P2 | A-PAPR-2 P2 ^ |

^ - Full-face

A(All classes) = Organic vapours, B AUS or B1 = Acid gasses, B2 = Acid gas or hydrogen cyanide(HCN), B3 = Acid gas or hydrogen cyanide(HCN), E = Sulfur dioxide(SO2), G = Agricultural chemicals, K = Ammonia(NH3), Hg = Mercury, NO = Oxides of nitrogen, MB = Methyl bromide, AX = Low boiling point organic compounds(below 65 degC)

- Cartridge respirators should never be used for emergency ingress or in areas of unknown vapour concentrations or oxygen content.
- The wearer must be warned to leave the contaminated area immediately on detecting any odours through the respirator. The odour may indicate that the mask is not functioning properly, that the vapour concentration is too high, or that the mask is not properly fitted. Because of these limitations, only restricted use of cartridge respirators is considered appropriate.
- Cartridge performance is affected by humidity. Cartridges should be changed after 2 hr of continuous use unless it is determined that the humidity is less than 75%, in which case, cartridges can be used for 4 hr. Used cartridges should be discarded daily, regardless of the length of time used

SECTION 9 Physical and chemical properties

LE4140 H1 QUINPLEX Food Grade Gear Lubricant

Issue Date: 23/12/2022 Print Date: 29/10/2024

Information on basic physical and chemical properties

Version No: 9.1

| Appearance | Transparent liquid with a hydrocarbon-like odour; not miscible with water. | | |
|---|--|---|----------------|
| | | | |
| Physical state | Liquid | Relative density (Water = 1) | 0.89 |
| Odour | Not Available | Partition coefficient n- octanol / water | Not Available |
| Odour threshold | Not Available | Auto-ignition temperature (°C) | Not Available |
| pH (as supplied) | 6-8 | Decomposition temperature (°C) | Not Available |
| Melting point / freezing point (°C) | Not Available | Viscosity (cSt) | 440 |
| Initial boiling point and boiling range (°C) | Not Available | Molecular weight (g/mol) | Not Applicable |
| Flash point (°C) | 198 | Taste | Not Available |
| Evaporation rate | Not Available | Explosive properties | Not Available |
| Flammability | Not Applicable | Oxidising properties | Not Available |
| Upper Explosive Limit (%) | Not Available | Surface Tension (dyn/cm or mN/m) | Not Available |
| Lower Explosive Limit (%) | Not Available | Volatile Component (%vol) | Not Available |
| Vapour pressure (kPa) | Not Available | Gas group | Not Available |
| Solubility in water | Immiscible | pH as a solution (1%) | Not Available |
| Vapour density (Air = 1) | <1 | VOC g/L | Not Available |
| Heat of Combustion (kJ/g) | Not Available | Ignition Distance (cm) | Not Available |
| Flame Height (cm) | Not Available | Flame Duration (s) | Not Available |
| Enclosed Space Ignition Time Equivalent (s/m3) | Not Available | Enclosed Space Ignition Deflagration Density (g/m3) | Not Available |

SECTION 10 Stability and reactivity

| Reactivity | See section 7 |
|------------------------------------|--|
| Chemical stability | Unstable in the presence of incompatible materials. Product is considered stable. Hazardous polymerisation will not occur. |
| Possibility of hazardous reactions | See section 7 |
| Conditions to avoid | See section 7 |
| Incompatible materials | See section 7 |
| Hazardous decomposition products | See section 5 |

SECTION 11 Toxicological information

Information on toxicological effects

| Inhaled | There is some evidence to suggest that the material can cause respiratory irritation in some persons. The body's response to such irritation can cause further lung damage. Inhalation hazard is increased at higher temperatures. Inhalation of oil droplets or aerosols may cause discomfort and may produce chemical inflammation of the lungs. |
|--------------|--|
| Ingestion | Accidental ingestion of the material may be damaging to the health of the individual. |
| Skin Contact | There is some evidence to suggest that this material can cause inflammation of the skin on contact in some persons. Open cuts, abraded or irritated skin should not be exposed to this material The material may accentuate any pre-existing dermatitis condition |
| Eye | There is some evidence to suggest that this material can cause eye irritation and damage in some persons. |
| Chronic | Substance accumulation, in the human body, may occur and may cause some concern following repeated or long-term occupational exposure. Oil may contact the skin or be inhaled. Extended exposure can lead to eczema, inflammation of hair follicles, pigmentation of the face and warts on the soles of the feet. |

| LE | 4140 H1 QUINPLEX Food |
|----|-----------------------|
| | Grade Gear Lubricant |

| TOXICITY | IRRITATION |
|---------------|---------------|
| Not Available | Not Available |

Page **7** of **14** Issue Date: 23/12/2022 Print Date: 29/10/2024 Version No: 9.1 LE4140 H1 QUINPLEX Food Grade Gear Lubricant

| white mineral oil (petroleum) | Dermal (rabbit) LD50: >2000 mg/kg ^[1] | F |
|--|---|--|
| white mineral oil (petroleum) | | Eye: no adverse effect observed (not irritating) ^[1] |
| - I and the second seco | Inhalation (Rat) LC50: >4.5 mg/l4h ^[1] | Skin: no adverse effect observed (not irritating) ^[1] |
| | Oral (Rat) LD50: >5000 mg/kg ^[2] | |
| | TOXICITY | IRRITATION |
| distillates, petroleum, middle, | Dermal (rabbit) LD50: >2000 mg/kg ^[1] | Not Available |
| hydrotreated | Inhalation (Rat) LC50: 1.72 mg/l4h ^[1] | |
| | Oral (Rat) LD50: >5000 mg/kg ^[2] | |
| | TOXICITY | IRRITATION |
| | Dermal (rabbit) LD50: 1800 mg/kg ^[2] | Eye (Primate - monkey): 1204ppm/15H (intermittent) |
| | Inhalation (Rat) LC50: ~6.45 mg/l4h ^[1] | Eye (Rodent - guinea pig): 1204ppm/7H |
| | Oral (Rat) LD50: 800 mg/kg ^[2] | Eye (Rodent - rabbit): 1204ppm/7H |
| ethyl acrylate | | Eye (Rodent - rabbit): 45mg - Mild |
| | | Eye (Rodent - rat): 1204ppm/14H (intermittent) |
| | | Skin (Human - woman): 0.1%/48H |
| | | Skin (Rodent - rabbit): 10mg/24H - Mild |
| | | Skin (Rodent - rabbit): 500mg - Mild |
| | TOXICITY | IRRITATION |
| pentaerythritol | dermal (rat) LD50: 3160 mg/kg ^[2] | Eye: no adverse effect observed (not irritating) ^[1] |
| rabutylhydroxyhydrocinnamate | Inhalation (Rat) LC50: >1.95 mg/l4h ^[2] | Skin: no adverse effect observed (not irritating) ^[1] |
| | Oral (Rat) LD50: >2000 mg/kg ^[2] | |
| | TOXICITY | IRRITATION |
| | Dermal (rabbit) LD50: 2000 mg/kg ^[2] | Eye (Rodent - rabbit): 100mg |
| | Inhalation (Rat) LC50: >0.007 mg/l4h ^[2] | Eye: adverse effect observed (irritating) ^[1] |
| benzoic acid | Oral (Rat) LD50: 1700 mg/kg ^[2] | Skin (Human): 0.25%/1H |
| | | Skin (Human): 0.76%/40M - Mild |
| | | Skin (Human): 22mg/3D (intermittent) - Moderate |
| | | Skin: adverse effect observed (irritating) ^[1] |
| | TOXICITY | IRRITATION |
| | Dermal (rabbit) LD50: >177 mg/kg ^[1] | Eye (Rodent - rabbit): 500mg/24H - Mild |
| | Oral (Mouse) LD50; >5000 mg/kg ^[1] | Eye (Rodent - rabbit): 5mg - Severe |
| 2-ethylhexyl acrylate | | Eye: no adverse effect observed (not irritating) ^[1] |
| | | Skin (Rodent - rabbit): 10mg/24H - Severe |
| | | Skin (Rodent - rabbit): 20mg/24H - Moderate |
| | | Skin (Rodent - rabbit): 500mg - Mild |
| | | Skin: adverse effect observed (irritating) ^[1] |
| Legend: 1. Valo | lue obtained from Europe ECHA Registered Substanc | ees - Acute toxicity 2. Value obtained from manufacturer's SDS. |

WHITE MINERAL OIL (PETROLEUM)

Oral (rat) TCLo: 92000 mg/kg/92D-Cont. Generally the toxicity and irritation is of low order. White oils and highly/solvent refined oils have not shown the long term risk of skin cancer that follows persistent skin contamination with some other mineral oils, due in all probability to refining that produces low content of both polyaromatics (PAH) and benz-alpha-pyrenes (BaP)

The substance is classified by IARC as Group 3:

NOT classifiable as to its carcinogenicity to humans.

Evidence of carcinogenicity may be inadequate or limited in animal testing.

DISTILLATES, PETROLEUM, MIDDLE, HYDROTREATED typical for isoparaffinic hydrocarbons: isoparaffinic hydrocarbon:

Chemwatch: 22-6148 Page 8 of 14

Issue Date: 23/12/2022 Version No. 9 1 Print Date: 29/10/2024 LE4140 H1 QUINPLEX Food Grade Gear Lubricant

Animal studies indicate that normal, branched and cyclic paraffins are absorbed from the gastrointestinal tract

and that the absorption of n-paraffins is inversely proportional to the carbon chain length, with little absorption above C30. With respect to the carbon chain lengths likely to be present in mineral oil, n-paraffins may be absorbed to a greater extent than iso- or cyclo-paraffins. The major classes of hydrocarbons are well absorbed into the gastrointestinal tract in various species. In many cases, the hydrophobic hydrocarbons are ingested in association with fats in the diet. Some hydrocarbons may appear unchanged as in the lipoprotein particles in the gut lymph, but most hydrocarbons partly separate from fats and undergo metabolism in the gut cell. The material may be irritating to the eye, with prolonged contact causing inflammation. Repeated or prolonged exposure to irritants may produce conjunctivitis. ETHYL ACRYLATE WARNING: This substance has been classified by the IARC as Group 2B: Possibly Carcinogenic to Humans. Tenth Annual Report on Carcinogens: Substance anticipated to be Carcinogen [National Toxicology Program: U.S. Dep. of Health & Human Services 2002] Non-sensitising in Guinea pig skin assay ** * CG ** Clariant PENTAERYTHRITOL Data show that acute toxicity following oral and topical use of hindered phenols is low. They are not proven to TETRABUTYLHYDROXYHYDROCINNAMATE cause mutations. However, long term use may affect the liver, thyroid, kidney and lymph nodes. Liver tumours have been reported. Mutagenicity: Bacterial reverse mutation test (S. typhimurium): not mutagenic (OECD 471, EC B.13/14; Ames test) In vitro mammalian chromosome aberration (Chinese hamster fibroblasts): negative Reproductive toxicity: 4 generation study in rats: Oral NOAEL >500 mg/kg bw/day STOT single exposure: In a repeated inhalation study benzoic acid appeared to be irritating to the respiratory tract at high doses * DSM SDS Benzyl alcohol, benzoic acid and its sodium and potassium salt have a common metabolic and excretion pathway. All but benzyl alcohol are considered to be unharmful and of low acute toxicity. They may cause BENZOIC ACID slight irritation by oral, dermal or inhalation exposure except sodium benzoate which doesn't irritate the skin. Studies showed increased mortality, reduced weight gain, liver and kidney effects at higher doses, also, lesions of the brains, thymus and skeletal muscles may occur with benzyl alcohol. This is a member or analogue of a group of benzyl derivatives generally regarded as safe (GRAS), based partly on their self-limiting properties as flavouring substances in food. In humans and other animals, they are rapidly absorbed, broken down and excreted, with a wide safety margin. They also lack significant potential to cause genetic toxicity and mutations. The intake of benzyl derivatives as natural components of traditional foods is actually higher than the intake as intentionally added flavouring substances. Substance has been investigated as a tumourigen on mouse skin. The material may cause severe skin irritation after prolonged or repeated exposure and may produce on contact skin redness, swelling, the production of vesicles, scaling and thickening of the skin. Repeated exposures may produce severe ulceration. 2-ETHYLHEXYL ACRYLATE For 2-ethylhexyl acrylate: Animal testing shows that 2-ethylhexyl acrylate can cause skin sensitisation and damage sensation of smell, and that chronic exposure can increase the incidence of kidney inflammation. High doses may cause developmental effects. Testing has shown that 2-ethylhexyl acrylate may cause genetic damage and/or mutations. It has not been shown to cause tumours except at very high doses. For highly and severely refined distillate base oils: In animal studies, the acute, oral, semilethal dose is >5g/kg body weight and the semilethal dose by skin contact is >2g/kg body weight. The semilethal concentration for inhalation is 2.18 to >4 mg/L. The materials have varied from "non-irritating" to "moderately irritating" when tested for skin and eye irritation. Testing for sensitisation has been negative. The materials included in the Lubricating Base Oils category are related from both process and physicalchemical perspectives: The potential toxicity of a specific distillate base oil is inversely related to the severity or extent of processing the oil has undergone, since: • The adverse effects of these materials are associated with undesirable components, and The levels of the undesirable components are inversely related to the degree of processing: WHITE MINERAL OIL (PETROLEUM) & • Distillate base oils receiving the same degree or extent of processing will have similar toxicities; DISTILLATES, PETROLEUM, MIDDLE, • The potential toxicity of residual base oils is independent of the degree of processing the oil receives. HYDROTREATED • The reproductive and developmental toxicity of the distillate base oils is inversely related to the degree of Unrefined & mildly refined distillate base oils contain the highest levels of undesirable components, have the largest variation of hydrocarbon molecules and have shown the highest potential cancer-causing and mutation-causing activities. Highly and severely refined distillate base oils are produced from unrefined and mildly refined oils by removing or transforming undesirable components. In comparison to unrefined and mildly refined base oils, the highly and severely refined distillate base oils have a smaller range of hydrocarbon molecules and have demonstrated very low mammalian toxicity. Testing of residual oils for mutation-causing and cancer-causing potential has shown negative results, supporting the belief that these materials lack biologically active components or the components are largely non-bioavailable due to their molecular size. Toxicity testing has consistently shown that lubricating base oils have low acute toxicities. ETHYL ACRYLATE & 2-ETHYLHEXYL The following information refers to contact allergens as a group and may not be specific to this product. ACRYLATE Contact allergies quickly manifest themselves as contact eczema, more rarely as urticaria or Quincke's oedema. The pathogenesis of contact eczema involves a cell-mediated (T lymphocytes) immune reaction of the delayed type. Other allergic skin reactions, e.g. contact urticaria, involve antibody-mediated immune reactions Where no "official" classification for acrylates and methacrylates exists, there have been cautious attempts to create classifications in the absence of contrary evidence. For example

> Monalkyl or monoarylesters of acrylic acids should be classified as R36/37/38 and R51/53 Monoalkyl or monoaryl esters of methacrylic acid should be classified as R36/37/38

Chemwatch: 22-6148 Version No: 9.1

LE4140 H1 QUINPLEX Food Grade Gear Lubricant

Issue Date: 23/12/2022 Print Date: 29/10/2024

| | | Based on the available oncogenicity data and without a better the Health and Environmental Review Division (HERD), Office previously concluded that all chemicals that contain the acrylat CH2=C(CH3)COO) should be considered to be a carcinogenic testing. This position has now been revised and acrylates and methaci | of Toxic Substances (OTS), of the US EPA te or methacrylate moiety (CH2=CHCOO or chazard unless shown otherwise by adequate | |
|--------------------------------------|--------------------------------|--|---|--|
| ETHYL ACRYLATE & BEN ETHYLHE | ZOIC ACID & 2- KYL ACRYLATE | Asthma-like symptoms may continue for months or even years be due to a non-allergic condition known as reactive airways d after exposure to high levels of highly irritating compound. Mai absence of previous airways disease in a non-atopic individual symptoms within minutes to hours of a documented exposure RADS include a reversible airflow pattern on lung function test on methacholine challenge testing, and the lack of minimal lym | ysfunction syndrome (RADS) which can occur n criteria for diagnosing RADS include the l, with sudden onset of persistent asthma-like to the irritant. Other criteria for diagnosis of s, moderate to severe bronchial hyperreactivity | |
| ETHYL ACRYLATE & BENZOIC ACID | | The material may cause skin irritation after prolonged or repeated exposure and may produce on contact skin redness, swelling, the production of vesicles, scaling and thickening of the skin. | | |
| BENZOIC ACID & 2 | 2-ETHYLHEXYL ACRYLATE | The material may produce severe irritation to the eye causing pronounced inflammation. Repeated or prolonged exposure to irritants may produce conjunctivitis. | | |
| Acute Toxicity | × | Coveline resultifu | × | |
| Skin Irritation/Corrosion | × | Carcinogenicity Reproductivity | × | |
| Serious Eye Damage/Irritation | × | STOT - Single Exposure | × | |
| Respiratory or Skin sensitisation | × | STOT - Repeated Exposure | × | |
| Mutagenicity | × | Aspiration Hazard | × | |

Legend:

🗶 – Data either not available or does not fill the criteria for classification

SECTION 12 Ecological information

Toxicity

| LE4140 H1 QUINPLEX Food Grade Gear Lubricant white mineral oil (petroleum) | Endpoint | Test Duration (hr) | Species | Value | Source |
|--|------------------|--------------------|-------------------------------|------------------|------------------|
| | Not Available | Not Available | Not Available | Not Available | Not Available |
| | Endpoint | Test Duration (hr) | Species | Value | Source |
| | LC50 | 96h | Fish | >10000mg/L | 2 |
| distillates, petroleum, middle, | Endpoint | Test Duration (hr) | Species | Value | Source |
| hydrotreated | NOEC(ECx) | 72h | Algae or other aquatic plants | <0.03mg/l | 1 |
| | Endpoint | Test Duration (hr) | Species | Value | Source |
| | EC50 | 72h | Algae or other aquatic plants | 1.71mg/l | 2 |
| | EC50 | 48h | Crustacea | 4.4mg/l | 1 |
| ethyl acrylate | LC50 | 96h | Fish | 2mg/l | 2 |
| | NOEC(ECx) | 504h | Crustacea | 0.19mg/l | 1 |
| | EC50 | 96h | Algae or other aquatic plants | 5.5mg/l | 2 |
| | Endpoint | Test Duration (hr) | Species | Value | Source |
| | BCF | 1008h | Fish | <0.2 | 7 |
| pentaerythritol | EC50 | 72h | Algae or other aquatic plants | >100mg/l | 1 |
| tetrabutylhydroxyhydrocinnamate | EC50(ECx) | 24h | Crustacea | >86mg/l | 1 |
| | LC50 | 96h | Fish | >100mg/l | Not Available |
| | Endpoint | Test Duration (hr) | Species | Value | Source |
| | EC50 | 72h | Algae or other aquatic plants | 0.14mg/L | 4 |
| benzoic acid | EC50 | 48h | Crustacea | >120mg/l | 2 |
| | NOEC(ECx) | 72h | Algae or other aquatic plants | 0.11mg/l | 2 |
| | 1.050 | 96h | Fish | 44.6mg/l | 2 |
| | LC50 | 3011 | | | |

Chemwatch: 22-6148 Page 10 of 14 Issue Date: 23/12/2022 Version No: 9.1

LE4140 H1 QUINPLEX Food Grade Gear Lubricant

Print Date: 29/10/2024

| LC50 | 96h | Fish | 1.1mg/l | 2 |
|-----------|------|-------------------------------|-----------|---|
| EC50 | 72h | Algae or other aquatic plants | 1.71mg/l | 2 |
| NOEC(ECx) | 504h | Crustacea | 0.136mg/l | 2 |
| EC50 | 48h | Crustacea | 1.3mg/l | 2 |
| EC50 | 96h | Algae or other aquatic plants | 2.65mg/l | 2 |

Leaend:

Extracted from 1. IUCLID Toxicity Data 2. Europe ECHA Registered Substances - Ecotoxicological Information - Aquatic Toxicity 4. US EPA, Ecotox database - Aquatic Toxicity Data 5. ECETOC Aquatic Hazard Assessment Data 6. NITE (Japan) -Bioconcentration Data 7. METI (Japan) - Bioconcentration Data 8. Vendor Data

DO NOT discharge into sewer or waterways.

Persistence and degradability

| Ingredient | Persistence: Water/Soil | Persistence: Air |
|--|---------------------------|-----------------------------|
| ethyl acrylate | LOW (Half-life = 14 days) | LOW (Half-life = 0.95 days) |
| pentaerythritol tetrabutylhydroxyhydrocinnamate | HIGH | HIGH |
| benzoic acid | LOW | LOW |
| 2-ethylhexyl acrylate | LOW | LOW |

Bioaccumulative potential

| Ingredient | Bioaccumulation |
|--|---------------------|
| ethyl acrylate | LOW (LogKOW = 1.32) |
| pentaerythritol tetrabutylhydroxyhydrocinnamate | LOW (BCF = 2.3) |
| benzoic acid | LOW (LogKOW = 1.87) |
| 2-ethylhexyl acrylate | LOW (BCF = 289.73) |

Mobility in soil

| Ingredient | Mobility |
|-----------------------|-----------------------|
| ethyl acrylate | LOW (Log KOC = 11.85) |
| benzoic acid | LOW (Log KOC = 14.49) |
| 2-ethylhexyl acrylate | LOW (Log KOC = 429) |

SECTION 13 Disposal considerations

disposal

Waste treatment methods

Legislation addressing waste disposal requirements may differ by country, state and/ or territory. Each user must refer to laws operating in their area. In some areas, certain wastes must be tracked.

A Hierarchy of Controls seems to be common - the user should investigate:

- Reduction
- Reuse
- ▶ Recycling
- Disposal (if all else fails) **Product / Packaging**

This material may be recycled if unused, or if it has not been contaminated so as to make it unsuitable for its intended use.

- DO NOT allow wash water from cleaning or process equipment to enter drains.
- It may be necessary to collect all wash water for treatment before disposal.
- In all cases disposal to sewer may be subject to local laws and regulations and these should be considered first.
- Where in doubt contact the responsible authority.
- Recycle wherever possible or consult manufacturer for recycling options.
- ▶ Consult State Land Waste Authority for disposal.
- ▶ Bury or incinerate residue at an approved site.
- · Recycle containers if possible, or dispose of in an authorised landfill.

Ensure that the hazardous substance is disposed in accordance with the Hazardous Substances (Disposal) Notice 2017

Disposal Requirements

Not applicable as substance/ material is non hazardous.

SECTION 14 Transport information

LE4140 H1 QUINPLEX Food Grade Gear Lubricant

Issue Date: 23/12/2022 Print Date: 29/10/2024

Labels Required

Version No: 9.1

| Marine Pollutant | NO |
|------------------|----------------|
| HAZCHEM | Not Applicable |

Land transport (UN): NOT REGULATED FOR TRANSPORT OF DANGEROUS GOODS

Air transport (ICAO-IATA / DGR): NOT REGULATED FOR TRANSPORT OF DANGEROUS GOODS

Sea transport (IMDG-Code / GGVSee): NOT REGULATED FOR TRANSPORT OF DANGEROUS GOODS

14.7.1. Transport in bulk according to Annex II of MARPOL and the IBC code

Not Applicable

14.7.2. Transport in bulk in accordance with MARPOL Annex V and the IMSBC Code

| Product name | Group |
|--|---------------|
| white mineral oil (petroleum) | Not Available |
| distillates, petroleum, middle, hydrotreated | Not Available |
| ethyl acrylate | Not Available |
| pentaerythritol tetrabutylhydroxyhydrocinnamate | Not Available |
| benzoic acid | Not Available |
| 2-ethylhexyl acrylate | Not Available |

14.7.3. Transport in bulk in accordance with the IGC Code

| Product name | Ship Type |
|--|---------------|
| white mineral oil (petroleum) | Not Available |
| distillates, petroleum, middle, hydrotreated | Not Available |
| ethyl acrylate | Not Available |
| pentaerythritol tetrabutylhydroxyhydrocinnamate | Not Available |
| benzoic acid | Not Available |
| 2-ethylhexyl acrylate | Not Available |

SECTION 15 Regulatory information

Safety, health and environmental regulations / legislation specific for the substance or mixture

This substance is to be managed using the conditions specified in an applicable Group Standard

| HSR Number | Group Standard |
|----------------|----------------|
| Not Applicable | Not Applicable |

Please refer to Section 8 of the SDS for any applicable tolerable exposure limit or Section 12 for environmental exposure limit.

white mineral oil (petroleum) is found on the following regulatory lists

Chemical Footprint Project - Chemicals of High Concern List

International Agency for Research on Cancer (IARC) - Agents Classified by the IARC Monographs

International Agency for Research on Cancer (IARC) - Agents Classified by the IARC Monographs - Group 1: Carcinogenic to humans

International Agency for Research on Cancer (IARC) - Agents Classified by the IARC Monographs - Not Classified as Carcinogenic

New Zealand Approved Hazardous Substances with controls

New Zealand Hazardous Substances and New Organisms (HSNO) Act - Classification of Chemicals

New Zealand Inventory of Chemicals (NZIoC)

New Zealand Workplace Exposure Standards (WES)

distillates, petroleum, middle, hydrotreated is found on the following regulatory lists

Chemical Footprint Project - Chemicals of High Concern List

International Agency for Research on Cancer (IARC) - Agents Classified by the IARC Monographs - Not Classified as Carcinogenic

New Zealand Approved Hazardous Substances with controls

New Zealand Hazardous Substances and New Organisms (HSNO) Act - Classification of Chemicals

Version No. 9.1

Page 12 of 14 Issue Date: 23/12/2022 Print Date: 29/10/2024 LE4140 H1 QUINPLEX Food Grade Gear Lubricant

New Zealand Inventory of Chemicals (NZIoC)

New Zealand Workplace Exposure Standards (WES)

ethyl acrylate is found on the following regulatory lists

Chemical Footprint Project - Chemicals of High Concern List

International Agency for Research on Cancer (IARC) - Agents Classified by the IARC Monographs

International Agency for Research on Cancer (IARC) - Agents Classified by the IARC Monographs - Group 2B: Possibly carcinogenic to humans

New Zealand Approved Hazardous Substances with controls

New Zealand Hazardous Substances and New Organisms (HSNO) Act - Classification of Chemicals

New Zealand Hazardous Substances and New Organisms (HSNO) Act - Classification of Chemicals - Classification Data

New Zealand Inventory of Chemicals (NZIoC)

New Zealand Workplace Exposure Standards (WES)

pentaerythritol tetrabutylhydroxyhydrocinnamate is found on the following regulatory lists

New Zealand Inventory of Chemicals (NZIoC)

benzoic acid is found on the following regulatory lists

International WHO List of Proposed Occupational Exposure Limit (OEL) Values for Manufactured Nanomaterials (MNMS)

New Zealand Hazardous Substances and New Organisms (HSNO) Act - Classification of Chemicals

New Zealand Hazardous Substances and New Organisms (HSNO) Act - Classification of Chemicals - Classification Data

New Zealand Inventory of Chemicals (NZIoC)

New Zealand Workplace Exposure Standards (WES)

2-ethylhexyl acrylate is found on the following regulatory lists

International Agency for Research on Cancer (IARC) - Agents Classified by the IARC Monographs

International Agency for Research on Cancer (IARC) - Agents Classified by the IARC Monographs - Group 2B: Possibly carcinogenic to humans

New Zealand Hazardous Substances and New Organisms (HSNO) Act - Classification of Chemicals

New Zealand Hazardous Substances and New Organisms (HSNO) Act - Classification of Chemicals - Classification Data

New Zealand Inventory of Chemicals (NZIoC)

New Zealand Land Transport Rule: Dangerous Goods 2005 - Schedule 4 Quantity Limits for Dangerous Goods in Excepted Quantities

New Zealand Land Transport Rule; Dangerous Goods 2005 - Schedule 2 Dangerous Goods in Limited Quantities and Consumer Commodities

Additional Regulatory Information

Not Applicable

Hazardous Substance Location

Subject to the Health and Safety at Work (Hazardous Substances) Regulations 2017.

| Hazard Class | Quantities |
|----------------|----------------|
| Not Applicable | Not Applicable |

Certified Handler

Subject to Part 4 of the Health and Safety at Work (Hazardous Substances) Regulations 2017.

| Class of substance | Quantities |
|--------------------|----------------|
| Not Applicable | Not Applicable |

Refer Group Standards for further information

Maximum quantities of certain hazardous substances permitted on passenger service vehicles

Subject to Regulation 13.14 of the Health and Safety at Work (Hazardous Substances) Regulations 2017.

| Hazard Class | Gas (aggregate water capacity in mL) | Liquid (L) | Solid (kg) | Maximum quantity per package for each classification |
|----------------|--------------------------------------|-------------------|-------------------|--|
| Not Applicable | Not Applicable | Not Applicable | Not Applicable | Not Applicable |

Tracking Requirements

Not Applicable

National Inventory Status

| National Inventory | Status |
|--|--------|
| Australia - AIIC / Australia Non-Industrial Use | Yes |
| Canada - DSL | Yes |

Chemwatch: 22-6148 Version No. 9.1

LE4140 H1 QUINPLEX Food Grade Gear Lubricant

Issue Date: 23/12/2022 Print Date: 29/10/2024

| National Inventory | Status |
|----------------------------------|--|
| Canada - NDSL | No (white mineral oil (petroleum); distillates, petroleum, middle, hydrotreated; ethyl acrylate; pentaerythritol tetrabutylhydroxyhydrocinnamate; benzoic acid; 2-ethylhexyl acrylate) |
| China - IECSC | Yes |
| Europe - EINEC / ELINCS / NLP | Yes |
| Japan - ENCS | Yes |
| Korea - KECI | Yes |
| New Zealand - NZIoC | Yes |
| Philippines - PICCS | Yes |
| USA - TSCA | All chemical substances in this product have been designated as TSCA Inventory 'Active' |
| Taiwan - TCSI | Yes |
| Mexico - INSQ | Yes |
| Vietnam - NCI | Yes |
| Russia - FBEPH | Yes |
| Legend: | Yes = All CAS declared ingredients are on the inventory No = One or more of the CAS listed ingredients are not on the inventory. These ingredients may be exempt or will require registration. |

SECTION 16 Other information

| Revision Date | 23/12/2022 |
|---------------|------------|
| Initial Date | 04/12/2009 |

SDS Version Summary

| Version | Date of Update | Sections Updated |
|---------|----------------|---|
| 8.1 | 19/09/2020 | Name |
| 9.1 | 23/12/2022 | Classification review due to GHS Revision change. |

Other information

Classification of the preparation and its individual components has drawn on official and authoritative sources as well as independent review by the Chemwatch Classification committee using available literature references.

The SDS is a Hazard Communication tool and should be used to assist in the Risk Assessment. Many factors determine whether the reported Hazards are Risks in the workplace or other settings. Risks may be determined by reference to Exposures Scenarios. Scale of use, frequency of use and current or available engineering controls must be considered.

Definitions and abbreviations

- PC TWA: Permissible Concentration-Time Weighted Average
- ▶ PC STEL: Permissible Concentration-Short Term Exposure Limit
- ▶ IARC: International Agency for Research on Cancer
- ACGIH: American Conference of Governmental Industrial Hygienists
- ▶ STEL: Short Term Exposure Limit
- ► TEEL: Temporary Emergency Exposure Limit。
- ▶ IDLH: Immediately Dangerous to Life or Health Concentrations
- ▶ ES: Exposure Standard
- OSF: Odour Safety Factor
- ▶ NOAEL: No Observed Adverse Effect Level
- LOAEL: Lowest Observed Adverse Effect Level
- ▶ TLV: Threshold Limit Value
- ▶ LOD: Limit Of Detection
- OTV: Odour Threshold Value
- ▶ BCF: BioConcentration Factors
- ▶ BEI: Biological Exposure Index
- ▶ DNFL: Derived No-Effect Level
- ▶ PNEC: Predicted no-effect concentration
- ▶ AIIC: Australian Inventory of Industrial Chemicals
- ▶ DSL: Domestic Substances List
- ▶ NDSL: Non-Domestic Substances List
- ▶ IECSC: Inventory of Existing Chemical Substance in China
- ▶ EINECS: European INventory of Existing Commercial chemical Substances
- ▶ ELINCS: European List of Notified Chemical Substances
- ▶ NLP: No-Longer Polymers

Chemwatch: 22-6148 Page **14** of **14** Issue Date: 23/12/2022 Version No: 9.1

LE4140 H1 QUINPLEX Food Grade Gear Lubricant

Print Date: 29/10/2024

- ▶ ENCS: Existing and New Chemical Substances Inventory
- ▶ KECI: Korea Existing Chemicals Inventory
- ▶ NZIoC: New Zealand Inventory of Chemicals
- ▶ PICCS: Philippine Inventory of Chemicals and Chemical Substances
- ▶ TSCA: Toxic Substances Control Act
- ▶ TCSI: Taiwan Chemical Substance Inventory
- ▶ INSQ: Inventario Nacional de Sustancias Químicas
- ▶ NCI: National Chemical Inventory
- ▶ FBEPH: Russian Register of Potentially Hazardous Chemical and Biological Substances

This document is copyright.

Apart from any fair dealing for the purposes of private study, research, review or criticism, as permitted under the Copyright Act, no part may be reproduced by any process without written permission from CHEMWATCH.

TEL (+61 3) 9572 4700.