

## LE1302 DUOLEC Vari-Purpose Gear Lubricant

## **Lubrication Engineers NZ Ltd**

Chemwatch: 22-7647 Version No: 8.1

Safety Data Sheet according to the Health and Safety at Work (Hazardous Substances) Regulations 2017

Chemwatch Hazard Alert Code: 2

Issue Date: 23/12/2022
Print Date: 29/10/2024
S.GHS.NZL.EN

## SECTION 1 Identification of the substance / mixture and of the company / undertaking

#### **Product Identifier**

Product name	LE1302 DUOLEC Vari-Purpose Gear Lubricant	
Chemical Name	lot Applicable	
Synonyms	Not Available	
Chemical formula	I formula Not Applicable	
Other means of identification	Not Available	

## Relevant identified uses of the substance or mixture and uses advised against

Relevant identified uses	Lubricant. Use according to manufacturer's directions.
--------------------------	---

#### Details of the manufacturer or supplier of the safety data sheet

Registered company name	Lubrication Engineers NZ Ltd		
Address	Address 11F Piermark Drive North Harbour Industrial Estate Albany, Auckland New Zealand		
Telephone	09 415 9411		
Fax +64 09 4158411			
Website	Website Not Available		
Email	Not Available		

## **Emergency telephone number**

Association / Organisation	Lubrication Engineers NZ Ltd	CHEMWATCH EMERGENCY RESPONSE (24/7)	
Emergency telephone number(s)	+64 21 3385487	+64 800 700 112	
Other emergency telephone number(s)	Not Available	+61 3 9573 3188	

Once connected and if the message is not in your preferred language then please dial 01

## **SECTION 2 Hazards identification**

## Classification of the substance or mixture

Considered a Hazardous Substance according to the criteria of the New Zealand Hazardous Substances New Organisms legislation. Not regulated for transport of Dangerous Goods.

## **Chemwatch Hazard Ratings**

	M	lin	Max	
Flammability	1			
Toxicity	0			
Body Contact	1			0 = Minimum 1 = Low
Reactivity	1			2 = Moderate
Chronic	2			3 = High 4 = Extreme

Classification [1]

Sensitisation (Skin) Category 1, Serious Eye Damage/Eye Irritation Category 1, Reproductive Toxicity Category 2, Hazardous to the Aquatic Environment Long-Term Hazard Category 3

Chemwatch: 22-7647 Version No: 8.1

#### LE1302 DUOLEC Vari-Purpose Gear Lubricant

Issue Date: 23/12/2022 Print Date: 29/10/2024

Legend:

1. Classified by Chemwatch; 2. Classification drawn from CCID EPA NZ; 3. Classification drawn from Regulation (EU) No 1272/2008 - Annex VI

Determined by Chemwatch using GHS/HSNO criteria

8.3A, 6.5B (contact), 6.8B, 9.1C

#### Label elements

## Hazard pictogram(s)







Signal word

Danger

## Hazard statement(s)

H317	May cause an allergic skin reaction.	
H318 Causes serious eye damage.		
H361 Suspected of damaging fertility or the unborn child.		
H412 Harmful to aquatic life with long lasting effects.		

## Precautionary statement(s) Prevention

P201	P201 Obtain special instructions before use.	
P280	Wear protective gloves, protective clothing, eye protection and face protection.	
P261 Avoid breathing mist/vapours/spray.		
P273	Avoid release to the environment.	

#### Precautionary statement(s) Response

P305+P351+P338 IF IN EYES: Rinse cautiously with water for several minutes. Remove contact lenses, if present and easy to do. Continuously with water for several minutes.		
P308+P313 IF exposed or concerned: Get medical advice/ attention.		
P310 Immediately call a POISON CENTER/doctor/physician/first aider.		
P302+P352 IF ON SKIN: Wash with plenty of water and soap.		

## Precautionary statement(s) Storage

, , , , , , , , , , , , , , , , , , , ,	,(-,g-		
P405	Store locked up.		

## Precautionary statement(s) Disposal

P501	Dispose of contents/container to authorised hazardous or special waste collection point in accordance with any local regulation.

## **SECTION 3 Composition / information on ingredients**

## Substances

See section below for composition of Mixtures

### **Mixtures**

CAS No	%[weight]	Name
8042-47-5	NotSpec	white mineral oil (petroleum)
91745-46-9	1-5	phosphoric acid ester amine salt
71-43-2	NotSpec	<u>benzene</u>
Not Available	balance	Ingredients determined not to be hazardous
Legend: 1. Classified by Chemwatch; 2. Classification drawn from CCID EPA NZ; 3. Classification drawn from Regulation (EU) No 1272/2008 - Annex VI; 4. Classification drawn from C&L * EU IOELVs available		

## **SECTION 4 First aid measures**

## Description of first aid measures

Eye Contact

If this product comes in contact with the eyes:

Chemwatch: 22-7647 Page 3 of 13 Issue Date: 23/12/2022 Version No: 8.1 Print Date: 29/10/2024

### LE1302 DUOLEC Vari-Purpose Gear Lubricant

	<ul> <li>Wash out immediately with fresh running water.</li> <li>Ensure complete irrigation of the eye by keeping eyelids apart and away from eye and moving the eyelids by occasionally lifting the upper and lower lids.</li> <li>Seek medical attention without delay; if pain persists or recurs seek medical attention.</li> <li>Removal of contact lenses after an eye injury should only be undertaken by skilled personnel.</li> </ul>
Skin Contact	If skin contact occurs:  Immediately remove all contaminated clothing, including footwear.  Flush skin and hair with running water (and soap if available).  Seek medical attention in event of irritation.
Inhalation	<ul> <li>If fumes, aerosols or combustion products are inhaled remove from contaminated area.</li> <li>Other measures are usually unnecessary.</li> </ul>
Ingestion	<ul> <li>Immediately give a glass of water.</li> <li>First aid is not generally required. If in doubt, contact a Poisons Information Centre or a doctor.</li> </ul>

## Indication of any immediate medical attention and special treatment needed

Treat symptomatically.

## **SECTION 5 Firefighting measures**

## **Extinguishing media**

- Water spray or fog.
- Alcohol stable foam.
- Dry chemical powder.
- Carbon dioxide.

Do not use a water jet to fight fire.

## Special hazards arising from the substrate or mixture

Fire Incompatibility	Fire Incompatibility  Avoid contamination with oxidising agents i.e. nitrates, oxidising acids, chlorine bleaches, pool chlorine etc. as ignition may result		
Advice for firefighters			
	▶ Alert Fire Brigade and tell them location and nature of hazard.		
Fire Fighting	<ul> <li>Wear full body protective clothing with breathing apparatus.</li> </ul>		
File Fighting	<ul><li>Prevent, by any means available, spillage from entering drains or water course.</li></ul>		

▶ Heating may cause expansion or decomposition leading to violent rupture of containers.

# Fire/Explosion Hazard

- Use water delivered as a fine spray to control fire and cool adjacent area.
- On combustion, may emit toxic fumes of carbon monoxide (CO). Combustion products include:

carbon dioxide (CO2)

phosphorus oxides (POx)

sulfur oxides (SOx)

▶ Combustible.

other pyrolysis products typical of burning organic material.

▶ Slight fire hazard when exposed to heat or flame.

May emit poisonous fumes.

#### **SECTION 6 Accidental release measures**

## Personal precautions, protective equipment and emergency procedures

See section 8

## **Environmental precautions**

See section 12

## Methods and material for containment and cleaning up

Minor Spills	<ul> <li>Remove all ignition sources.</li> <li>Clean up all spills immediately.</li> <li>Avoid breathing vapours and contact with skin and eyes.</li> <li>Control personal contact with the substance, by using protective equipment.</li> </ul>
Major Spills	<ul> <li>Clear area of personnel and move upwind.</li> <li>Alert Fire Brigade and tell them location and nature of hazard.</li> <li>Wear full body protective clothing with breathing apparatus.</li> <li>Prevent, by all means available, spillage from entering drains or water courses.</li> </ul>

Personal Protective Equipment advice is contained in Section 8 of the SDS.

Version No: 8.1

## LE1302 DUOLEC Vari-Purpose Gear Lubricant

Issue Date: 23/12/2022 Print Date: 29/10/2024

## **SECTION 7 Handling and storage**

## Precautions for safe handling

#### Safe handling

- ▶ DO NOT allow clothing wet with material to stay in contact with skin
- ▶ Avoid all personal contact, including inhalation.
- Wear protective clothing when risk of exposure occurs.
- Use in a well-ventilated area.
- Prevent concentration in hollows and sumps.
- Other information
- ▶ Store in original containers.
- ► Keep containers securely sealed.
- ▶ No smoking, naked lights or ignition sources.
- ▶ Store in a cool, dry, well-ventilated area.

#### Conditions for safe storage, including any incompatibilities

## Suitable container

- ▶ Metal can or drum
- ▶ Packaging as recommended by manufacturer.
- ▶ Check all containers are clearly labelled and free from leaks.

#### Storage incompatibility

Avoid reaction with oxidising agents















- Must not be stored together
- 0 May be stored together with specific preventions
- May be stored together

Note: Depending on other risk factors, compatibility assessment based on the table above may not be relevant to storage situations, particularly where large volumes of dangerous goods are stored and handled. Reference should be made to the Safety Data Sheets for each substance or article and risks assessed accordingly.

### **SECTION 8 Exposure controls / personal protection**

### **Control parameters**

## Occupational Exposure Limits (OEL)

## INGREDIENT DATA

Source	Ingredient	Material name	TWA	STEL	Peak	Notes
New Zealand Workplace Exposure Standards (WES)	white mineral oil (petroleum)	Oil mist, mineral	5 mg/m3	10 mg/m3	Not Available	(om) - Sampled by a method that does not collect vapour
New Zealand Workplace Exposure Standards (WES)	benzene	Benzene	0.05 ppm / 0.16 mg/m3	Not Available	Not Available	carcinogen category 1 - Known or presumed human carcinogen (skin) - Skin absorption

Ingredient	Original IDLH	Revised IDLH
white mineral oil (petroleum)	2,500 mg/m3	Not Available
phosphoric acid ester amine salt	Not Available	Not Available
benzene	500 ppm	Not Available

#### **Occupational Exposure Banding**

Ingredient	Occupational Exposure Band Rating	Occupational Exposure Band Limit	
phosphoric acid ester amine salt	E	≤ 0.01 mg/m³	
Notes:	Occupational exposure banding is a process of assigning chemicals into specific categories or bands based on a chemical's potency and the adverse health outcomes associated with exposure. The output of this process is an occupational exposure band (OEB), which corresponds to a range of exposure concentrations that are expected to protect worker health.		

## **Exposure controls**

## Appropriate engineering controls

Engineering controls are used to remove a hazard or place a barrier between the worker and the hazard. Well-designed engineering controls can be highly effective in protecting workers and will typically be independent of worker interactions to provide this high level of protection.

The basic types of engineering controls are:

Process controls which involve changing the way a job activity or process is done to reduce the risk.

Chemwatch: 22-7647 Page 5 of 13

#### LE1302 DUOLEC Vari-Purpose Gear Lubricant

Issue Date: 23/12/2022 Print Date: 29/10/2024

Enclosure and/or isolation of emission source which keeps a selected hazard "physically" away from the worker and ventilation that strategically "adds" and "removes" air in the work environment. Individual protection measures, such as personal protective equipment Safety glasses with side shields. Chemical goggles, [AS/NZS 1337.1, EN166 or national equivalent] Eye and face protection ▶ Contact lenses may pose a special hazard; soft contact lenses may absorb and concentrate irritants. A written policy document, describing the wearing of lenses or restrictions on use, should be created for each workplace or task, Skin protection See Hand protection below ▶ Wear chemical protective gloves, e.g. PVC. Wear safety footwear or safety gumboots, e.g. Rubber NOTE: ▶ The material may produce skin sensitisation in predisposed individuals. Care must be taken, when removing gloves and other protective equipment, to avoid all possible skin contact. Contaminated leather items, such as shoes, belts and watch-bands should be removed and destroyed. Hands/feet protection The selection of suitable gloves does not only depend on the material, but also on further marks of quality which vary from manufacturer to manufacturer. Where the chemical is a preparation of several substances, the resistance of the glove material can not be calculated in advance and has therefore to be checked prior to the application. The exact break through time for substances has to be obtained from the manufacturer of the protective gloves and has to be observed when making a final choice. Personal hygiene is a key element of effective hand care. See Other protection below **Body protection** 

#### Recommended material(s)

Version No: 8.1

## **GLOVE SELECTION INDEX**

Glove selection is based on a modified presentation of the:

## "Forsberg Clothing Performance Index".

Other protection

The effect(s) of the following substance(s) are taken into account in the *computer-generated* selection:

Overalls.P.V.C apron.

Barrier cream.Skin cleansing cream.

LE1302 DUOLEC Vari-Purpose Gear Lubricant

Material	СРІ
PE/EVAL/PE	A
PVA	A
TEFLON	A
VITON	A
VITON/NEOPRENE	А
BUTYL	С
BUTYL/NEOPRENE	С
NATURAL RUBBER	С
NEOPRENE	С
NITRILE	С
NITRILE+PVC	С
PVC	С

- \* CPI Chemwatch Performance Index
- A: Best Selection
- B: Satisfactory; may degrade after 4 hours continuous immersion
- C: Poor to Dangerous Choice for other than short term immersion

**NOTE**: As a series of factors will influence the actual performance of the glove, a final selection must be based on detailed observation. -

\* Where the glove is to be used on a short term, casual or infrequent basis, factors such as "feel" or convenience (e.g. disposability), may dictate a choice of gloves which might otherwise be unsuitable following long-term or frequent use. A qualified practitioner should be consulted.

## **Ansell Glove Selection**

Glove — In order of recommendation	1
AlphaTec® 38-612	1

#### Respiratory protection

Type A-P Filter of sufficient capacity. (AS/NZS 1716 & 1715, EN 143:2000 & 149:2001, ANSI Z88 or national equivalent)

Where the concentration of gas/particulates in the breathing zone, approaches or exceeds the "Exposure Standard" (or ES), respiratory protection is required. Degree of protection varies with both face-piece and Class of filter; the nature of protection varies with Type of filter.

Required Minimum Protection Factor	Half-Face Respirator	Full-Face Respirator	Powered Air Respirator
up to 10 x ES	A-AUS P2	-	A-PAPR-AUS / Class 1 P2
up to 50 x ES	-	A-AUS / Class 1 P2	-
up to 100 x ES	-	A-2 P2	A-PAPR-2 P2 ^

#### ^ - Full-face

A(All classes) = Organic vapours, B AUS or B1 = Acid gasses, B2 = Acid gas or hydrogen cyanide(HCN), B3 = Acid gas or hydrogen cyanide(HCN), E = Sulfur dioxide(SO2), G = Agricultural chemicals, K = Ammonia(NH3), Hg = Mercury, NO = Oxides of nitrogen, MB = Methyl bromide, AX = Low boiling point organic compounds(below 65 degC)

- Cartridge respirators should never be used for emergency ingress or in areas of unknown vapour concentrations or oxygen content.
- The wearer must be warned to leave the contaminated area immediately on detecting any odours through the respirator. The odour may indicate that the mask is not functioning properly, that the vapour concentration is too high, or that the mask is not properly fitted. Because of these limitations, only restricted use of cartridge respirators is considered appropriate.
- Cartridge performance is affected by humidity. Cartridges should be changed after 2 hr of continuous use unless it is determined that the humidity is less than 75%, in which case, cartridges can be used for 4 hr. Used cartridges should be discarded daily, regardless of the length of time

Page 6 of 13 Chemwatch: 22-7647

Version No: 8.1 LE1302 DUOLEC Vari-Purpose Gear Lubricant

Issue Date: 23/12/2022 Print Date: 29/10/2024

AlphaTec® 15-554 AlphaTec® Solvex® 37-185 AlphaTec® 58-008 AlphaTec® 58-530B AlphaTec® 58-530W AlphaTec® Solvex® 37-675 AlphaTec® 58-735 AlphaTec® 79-700 AlphaTec® 53-001

The suggested gloves for use should be confirmed with the glove supplier.

## **SECTION 9 Physical and chemical properties**

## Information on basic physical and chemical properties

Appearance	Amber liquid with a hydrocarbon odour; not miscible with water.				
Physical state	Liquid	Relative density (Water = 1)	0.85		
Odour	Not Available	Partition coefficient n- octanol / water	Not Available		
Odour threshold	Not Available	Auto-ignition temperature (°C)	Not Available		
pH (as supplied)	6-8	Decomposition temperature (°C)	Not Available		
Melting point / freezing point (°C)	Not Available	Viscosity (cSt)	70.75		
Initial boiling point and boiling range (°C)	Not Available	Molecular weight (g/mol)	Not Applicable		
Flash point (°C)	207	Taste	Not Available		
Evaporation rate	Not Available	Explosive properties	Not Available		
Flammability	Not Applicable	Oxidising properties	Not Available		
Upper Explosive Limit (%)	Not Available	Surface Tension (dyn/cm or mN/m)	Not Available		
Lower Explosive Limit (%)	Not Available	Volatile Component (%vol)	Not Available		
Vapour pressure (kPa)	Not Available	Gas group	Not Available		
Solubility in water	Immiscible	pH as a solution (1%)	Not Available		
Vapour density (Air = 1)	<1	VOC g/L	Not Available		
Heat of Combustion (kJ/g)	Not Available	Ignition Distance (cm)	Not Available		
Flame Height (cm)	Not Available	Flame Duration (s)	Not Available		
Enclosed Space Ignition Time Equivalent (s/m3)	Not Available	Enclosed Space Ignition Deflagration Density (g/m3)	Not Available		

## **SECTION 10 Stability and reactivity**

Reactivity	See section 7
Chemical stability	<ul> <li>Unstable in the presence of incompatible materials.</li> <li>Product is considered stable.</li> <li>Hazardous polymerisation will not occur.</li> </ul>
Possibility of hazardous reactions	See section 7
Conditions to avoid	See section 7
Incompatible materials	See section 7
Hazardous decomposition products	See section 5

## **SECTION 11 Toxicological information**

Version No: 8.1

#### LE1302 DUOLEC Vari-Purpose Gear Lubricant

Issue Date: 23/12/2022 Print Date: 29/10/2024

Inhaled	There is some evidence to suggest that the material can cause respiratory irritation in some persons. The body's response to such irritation can cause further lung damage. Inhalation hazard is increased at higher temperatures.			
Ingestion	The material has <b>NOT</b> been classified by EC Directives or other classification systems as "harmful by ingestion". This is because of the lack of corroborating animal or human evidence.			
Skin Contact	There is some evidence to suggest that this material compen cuts, abraded or irritated skin should not be expo	an cause inflammation of the skin on contact in some persons.  sed to this material		
Eye	This material can cause eye irritation and damage in s	ome persons.		
Chronic	Skin contact with the material is more likely to cause a sensitisation reaction in some persons compared to the general population.  Ample evidence from experiments exists that there is a suspicion this material directly reduces fertility.  Substance accumulation, in the human body, may occur and may cause some concern following repeated or long-term occupational exposure.  This material can be regarded as being able to cause cancer in humans based on experiments and other information.  Chronic exposure to benzene may cause headache, fatigue, loss of appetite and lassitude with incipient blood effects including anaemia and blood changes. Benzene is a myelotoxicant known to suppress bone- marrow cell proliferation and to induce haematologic disorders in humans and animals.			
1 E4000 BHOLEO V	тохісіту	IRRITATION		
LE1302 DUOLEC Vari- Purpose Gear Lubricant	Not Available	Not Available		
	TOXICITY	IRRITATION		
white mineral oil	Dermal (rabbit) LD50: >2000 mg/kg <sup>[1]</sup>	Eye: no adverse effect observed (not irritating) <sup>[1]</sup>		
(petroleum)	Inhalation (Rat) LC50: >4.5 mg/l4h <sup>[1]</sup>	Skin: no adverse effect observed (not irritating) <sup>[1]</sup>		
	Oral (Rat) LD50: >5000 mg/kg <sup>[2]</sup>			
phosphoric acid ester	TOXICITY	IRRITATION		
amine salt	Not Available	Not Available		
	тохісіту	IRRITATION		
	dermal (mouse) LD50: 48 mg/kg <sup>[2]</sup>	Eye (Rodent - rabbit): 0.1mL		
	Inhalation (Rat) LC50: 43.767 mg/L4h <sup>[1]</sup>	Eye (Rodent - rabbit): 0.1mL - Severe		
	Oral (Rat) LD50: 930 mg/kg <sup>[2]</sup>	Eye (Rodent - rabbit): 2mg/24H - Severe		
benzene		Eye (Rodent - rabbit): 88mg - Moderate		
30.120.10		Eye: adverse effect observed (irritating) <sup>[1]</sup>		
		Skin (Rodent - rabbit): 15mg/24H - Mild		
		Skin (Rodent - rabbit): 20mg/24H - Moderate		
		Skin (Rodent - rat): 60uL/8H - Mild		
		Skin: adverse effect observed (irritating) <sup>[1]</sup>		
Legend:	Value obtained from Europe ECHA Registered Subs Unless otherwise specified data extracted from RTEC	stances - Acute toxicity 2. Value obtained from manufacturer's SDS. S - Register of Toxic Effect of chemical Substances		

## WHITE MINERAL OIL (PETROLEUM)

Oral (rat) TCLo: 92000 mg/kg/92D-Cont. Generally the toxicity and irritation is of low order. White oils and highly/solvent refined oils have not shown the long term risk of skin cancer that follows persistent skin contamination with some other mineral oils, due in all probability to refining that produces low content of both polyaromatics (PAH) and benz-alpha-pyrenes (BaP) The substance is classified by IARC as Group 3:

NOT classifiable as to its carcinogenicity to humans.

Evidence of carcinogenicity may be inadequate or limited in animal testing.

For highly and severely refined distillate base oils:

In animal studies, the acute, oral, semilethal dose is >5g/kg body weight and the semilethal dose by skin contact is >2g/kg body weight. The semilethal concentration for inhalation is 2.18 to >4 mg/L. The materials have varied from "non-irritating" to "moderately irritating" when tested for skin and eye irritation. Testing for sensitisation has been negative.

The materials included in the Lubricating Base Oils category are related from both process and physical-chemical perspectives; The potential toxicity of a specific distillate base oil is inversely related to the severity or extent of processing the oil has undergone, since:

- The adverse effects of these materials are associated with undesirable components, and
- The levels of the undesirable components are inversely related to the degree of processing;
- Distillate base oils receiving the same degree or extent of processing will have similar toxicities;
- The potential toxicity of residual base oils is independent of the degree of processing the oil receives.

• The reproductive and developmental toxicity of the distillate base oils is inversely related to the degree of processing.

Unrefined & mildly refined distillate base oils contain the highest levels of undesirable components, have the largest variation of hydrocarbon molecules and have shown the highest potential cancer-causing and mutation-causing activities. Highly and severely refined distillate base oils are produced from unrefined and mildly refined oils by removing or transforming undesirable

Chemwatch: 22-7647 Page 8 of 13 Version No: 8.1

LE1302 DUOLEC Vari-Purpose Gear Lubricant

Issue Date: 23/12/2022 Print Date: 29/10/2024

	components. In comparison to unrefined and mildly refined base oils, the highly and severely refined distillate base oils have a smaller range of hydrocarbon molecules and have demonstrated very low mammalian toxicity. Testing of residual oils for mutation-causing and cancer-causing potential has shown negative results, supporting the belief that these materials lack biologically active components or the components are largely non-bioavailable due to their molecular size.  Toxicity testing has consistently shown that lubricating base oils have low acute toxicities.			
PHOSPHORIC ACID ESTER AMINE SALT	The oral administration of the substance to rats by gavage, for a period of up to fifty six consecutive days at dose levels of 15, 150 and 750 mglkglday (reduced to 500 mglkglday on Day 5) resulted in treatment-related reproductive effects at 500 and 150 mglkglday. The 'No Observed Effect Level' (NOEL) for reproductive toxicity was therefore considered to be 15 mglkglday.			
BENZENE	Inhalation (man) TCLo: 150 ppm/1y - I  Data demonstrate that during inhalation exposure, aromatic hydrocarbons undergo substantial partitioning into adipose tissues.  Following cessation of exposure, the level of aromatic hydrocarbons in body fats rapidly declines. Thus, the aromatic hydrocarbons are unlikely to bioaccumulate in the body. Selective partitioning of the aromatic hydrocarbons into the non-adipose tissues is unlikely.  The material may cause skin irritation after prolonged or repeated exposure and may produce on contact skin redness, swelling, the production of vesicles, scaling and thickening of the skin.  WARNING: This substance has been classified by the IARC as Group 1: CARCINOGENIC TO HUMANS.			
LE1302 DUOLEC Vari- Purpose Gear Lubricant & PHOSPHORIC ACID ESTER AMINE SALT	The following information refers to contact allergens as a group and may not be specific to this product.  Contact allergies quickly manifest themselves as contact eczema, more rarely as urticaria or Quincke's oedema. The pathogenesis of contact eczema involves a cell-mediated (T lymphocytes) immune reaction of the delayed type. Other allergic skin reactions, e.g. contact urticaria, involve antibody-mediated immune reactions. No significant acute toxicological data identified in literature search.			
Acute Toxicity	X Carcinogenicity	×		
Skin Irritation/Corrosion	X Reproductivity	· •		
Serious Eye Damage/Irritation	✓ STOT - Single Exposure	×		
Respiratory or Skin sensitisation	✓ STOT - Repeated Exposure	×		
Mutagenicity	X Aspiration Hazard	X		

Legend: 🗶 – Data either not available or does not fill the criteria for classification ✓ – Data available to make classification

## **SECTION 12 Ecological information**

## **Toxicity**

LE1302 DUOLEC Vari- Purpose Gear Lubricant	Endpoint	Test Duration (hr)	Species	Value	Source
	Not Available	Not Available	Not Available	Not Available	Not Available
white mineral oil	Endpoint	Test Duration (hr)	Species	Value	Source
(petroleum)	LC50	96h	Fish	>10000mg/L	2
	Endpoint	Test Duration (hr)	Species	Value	Source
phosphoric acid ester amine salt	Not Available	Not Available	Not Available	Not Available	Not Available
	Endpoint	Test Duration (hr)	Species	Value	Sourc
	ErC50	72h	Algae or other aquatic plants	>1360mg/l	1
	EC50	72h	Algae or other aquatic plants	29mg/l	1
benzene	EC50	48h	Crustacea	7.578- 13.983mg/L	4
	LC50	96h	Fish	2.54- 7.217mg/L	4
	EC50	96h	Algae or other aquatic plants	>1360mg/I	1
	EC50(ECx)	24h	Algae or other aquatic plants	<0.001mg/L	4
Legend:	4. US EPA, E		pe ECHA Registered Substances - Ecotoxicologi Data 5. ECETOC Aquatic Hazard Assessment D	•	

Harmful to aquatic organisms, may cause long-term adverse effects in the aquatic environment.

Do NOT allow product to come in contact with surface waters or to intertidal areas below the mean high water mark. Do not contaminate water when cleaning equipment or disposing of equipment wash-waters.

Wastes resulting from use of the product must be disposed of on site or at approved waste sites.

DO NOT discharge into sewer or waterways.

Chemwatch: 22-7647 Page 9 of 13

Version No: 8.1 LE1302 DUOLEC Vari-Purpose Gear Lubricant

Page 9 of 13 Issue Date: 23/12/2022
Print Date: 29/10/2024

## Persistence and degradability

Ingredient	Persistence: Water/Soil	Persistence: Air
benzene	HIGH (Half-life = 720 days)	LOW (Half-life = 20.88 days)

#### Bioaccumulative potential

Ingredient	Bioaccumulation
benzene	HIGH (BCF = 4360)

## Mobility in soil

Ingredient	Mobility	
benzene	LOW (Log KOC = 165.5)	

#### **SECTION 13 Disposal considerations**

#### Waste treatment methods

- ▶ Containers may still present a chemical hazard/ danger when empty.
- Return to supplier for reuse/ recycling if possible.

#### Otherwise:

- If container can not be cleaned sufficiently well to ensure that residuals do not remain or if the container cannot be used to store the same product, then puncture containers, to prevent re-use, and bury at an authorised landfill.
- ▶ Where possible retain label warnings and SDS and observe all notices pertaining to the product.

Legislation addressing waste disposal requirements may differ by country, state and/ or territory. Each user must refer to laws operating in their area. In some areas, certain wastes must be tracked.

A Hierarchy of Controls seems to be common - the user should investigate:

## Product / Packaging disposal

- Reduction
- ReuseRecycling
- Disposal (if all else fails)
- This material may be recycled if unused, or if it has not been contaminated so as to make it unsuitable for its intended use.
- ▶ DO NOT allow wash water from cleaning or process equipment to enter drains.
- ▶ It may be necessary to collect all wash water for treatment before disposal.
- In all cases disposal to sewer may be subject to local laws and regulations and these should be considered first.
- Where in doubt contact the responsible authority.
- Recycle wherever possible or consult manufacturer for recycling options.
- Consult State Land Waste Authority for disposal.
- Bury or incinerate residue at an approved site.
- ▶ Recycle containers if possible, or dispose of in an authorised landfill.

Ensure that the hazardous substance is disposed in accordance with the Hazardous Substances (Disposal) Notice 2017

#### **Disposal Requirements**

Packages that have been in direct contact with the hazardous substance must be only disposed if the hazardous substance was appropriately removed and cleaned out from the package. The package must be disposed according to the manufacturer's directions taking into account the material it is made of. Packages which hazardous content have been appropriately treated and removed may be recycled.

The hazardous substance must only be disposed if it has been treated by a method that changed the characteristics or composition of the substance and it is no longer hazardous.

## **SECTION 14 Transport information**

## **Labels Required**

Marine Pollutant	NO
HAZCHEM	Not Applicable

Land transport (UN): NOT REGULATED FOR TRANSPORT OF DANGEROUS GOODS

Air transport (ICAO-IATA / DGR): NOT REGULATED FOR TRANSPORT OF DANGEROUS GOODS

Sea transport (IMDG-Code / GGVSee): NOT REGULATED FOR TRANSPORT OF DANGEROUS GOODS

14.7.1. Transport in bulk according to Annex II of MARPOL and the IBC code

Not Applicable

Page 10 of 13 Issue Date: 23/12/2022 Chemwatch: 22-7647 Version No: 8.1

## LE1302 DUOLEC Vari-Purpose Gear Lubricant

Print Date: 29/10/2024

## 14.7.2. Transport in bulk in accordance with MARPOL Annex V and the IMSBC Code

Product name	Group
white mineral oil (petroleum)	Not Available
phosphoric acid ester amine salt	Not Available
benzene	Not Available

## 14.7.3. Transport in bulk in accordance with the IGC Code

Product name	Ship Type
white mineral oil (petroleum)	Not Available
phosphoric acid ester amine salt	Not Available
benzene	Not Available

## **SECTION 15 Regulatory information**

## Safety, health and environmental regulations / legislation specific for the substance or mixture

This substance is to be managed using the conditions specified in an applicable Group Standard

HSR Number	Group Standard		
HSR002521	Animal Nutritional and Animal Care Products Group Standard 2020		
HSR002530	Cleaning Products Subsidiary Hazard Group Standard 2020		
HSR002535	Gases under Pressure Mixtures Subsidiary Hazard Group Standard 2020		
HSR002503	Additives Process Chemicals and Raw Materials Subsidiary Hazard Group Standard 2020		
HSR002606	Lubricants Lubricant Additives Coolants and Anti freeze Agents Subsidiary Hazard Group Standard 2020		
HSR002612	Metal Industry Products Subsidiary Hazard Group Standard 2020		
HSR002624	N.O.S. Subsidiary Hazard Group Standard 2020		
HSR002638	Photographic Chemicals Subsidiary Hazard Group Standard 2020		
HSR002644	Polymers Subsidiary Hazard Group Standard 2020		
HSR002647	Reagent Kits Group Standard 2020		
HSR002648	Refining Catalysts Group Standard 2020		
HSR002653	Solvents Subsidiary Hazard Group Standard 2020		
HSR002670	Surface Coatings and Colourants Subsidiary Hazard Group Standard 2020		
HSR002684	Water Treatment Chemicals Subsidiary Hazard Group Standard 2020		
HSR100425	Pharmaceutical Active Ingredients Group Standard 2020		
HSR002600	Leather and Textile Products Subsidiary Hazard Group Standard 2020		
HSR002544	Construction Products Subsidiary Hazard Group Standard 2020		
HSR002549	Corrosion Inhibitors Subsidiary Hazard Group Standard 2020		
HSR002552	Cosmetic Products Group Standard 2020		
HSR002558	Dental Products Subsidiary Hazard Group Standard 2020		
HSR002565	Embalming Products Subsidiary Hazard Group Standard 2020		
HSR002571	Fertilisers Subsidiary Hazard Group Standard 2020		
HSR002573	Fire Fighting Chemicals Group Standard 2021		
HSR002578	Food Additives and Fragrance Materials Subsidiary Hazard Group Standard 2020		
HSR002585	Fuel Additives Subsidiary Hazard Group Standard 2020		
HSR002596	Laboratory Chemicals and Reagent Kits Group Standard 2020		
HSR100757	Veterinary Medicines Limited Pack Size Finished Dose Group Standard 2020		
HSR100758	Veterinary Medicines Non dispersive Closed System Application Group Standard 2020		
HSR100759	Veterinary Medicines Non dispersive Open System Application Group Standard 2020		
HSR100592	Agricultural Compounds Special Circumstances Group Standard 2020		
HSR100756	Active Ingredients for Use in the Manufacture of Agricultural Compounds Group Standard 2020		

Please refer to Section 8 of the SDS for any applicable tolerable exposure limit or Section 12 for environmental exposure limit.

white mineral oil (petroleum) is found on the following regulatory lists

Chemical Footprint Project - Chemicals of High Concern List

Chemwatch: 22-7647 Version No: 8.1

#### LE1302 DUOLEC Vari-Purpose Gear Lubricant

Issue Date: 23/12/2022
Print Date: 29/10/2024

International Agency for Research on Cancer (IARC) - Agents Classified by the IARC Monographs

International Agency for Research on Cancer (IARC) - Agents Classified by the IARC Monographs - Group 1: Carcinogenic to humans

International Agency for Research on Cancer (IARC) - Agents Classified by the IARC Monographs - Not Classified as Carcinogenic

New Zealand Approved Hazardous Substances with controls

New Zealand Hazardous Substances and New Organisms (HSNO) Act - Classification of Chemicals

New Zealand Inventory of Chemicals (NZIoC)

New Zealand Workplace Exposure Standards (WES)

#### phosphoric acid ester amine salt is found on the following regulatory lists

New Zealand Inventory of Chemicals (NZIoC)

New Zealand Land Transport Rule: Dangerous Goods 2005 - Schedule 1 Quantity limits for dangerous goods

#### benzene is found on the following regulatory lists

Chemical Footprint Project - Chemicals of High Concern List

International Agency for Research on Cancer (IARC) - Agents Classified by the IARC Monographs

International Agency for Research on Cancer (IARC) - Agents Classified by the IARC Monographs - Group 1: Carcinogenic to humans

New Zealand Approved Hazardous Substances with controls

New Zealand Hazardous Substances and New Organisms (HSNO) Act - Classification of Chemicals

New Zealand Hazardous Substances and New Organisms (HSNO) Act - Classification of Chemicals - Classification Data

New Zealand Inventory of Chemicals (NZIoC)

New Zealand Workplace Exposure Standards (WES)

## **Additional Regulatory Information**

Not Applicable

## **Hazardous Substance Location**

Subject to the Health and Safety at Work (Hazardous Substances) Regulations 2017.

Hazard Class	Quantities
Not Applicable	Not Applicable

## Certified Handler

Subject to Part 4 of the Health and Safety at Work (Hazardous Substances) Regulations 2017.

Class of substance	Quantities
Not Applicable	Not Applicable

Refer Group Standards for further information

### Maximum quantities of certain hazardous substances permitted on passenger service vehicles

Subject to Regulation 13.14 of the Health and Safety at Work (Hazardous Substances) Regulations 2017.

Hazard Class	Gas (aggregate water capacity in mL)	Liquid (L)	Solid (kg)	Maximum quantity per package for each classification
6.5A or 6.5B	120	1	3	

## **Tracking Requirements**

Not Applicable

## **National Inventory Status**

National Inventory	Status		
Australia - AIIC / Australia Non-Industrial Use	Yes		
Canada - DSL	Yes		
Canada - NDSL	No (white mineral oil (petroleum); phosphoric acid ester amine salt; benzene)		
China - IECSC	No (phosphoric acid ester amine salt)		
Europe - EINEC / ELINCS / NLP	Yes		
Japan - ENCS	No (phosphoric acid ester amine salt)		
Korea - KECI	No (phosphoric acid ester amine salt)		
New Zealand - NZIoC	Yes		
Philippines - PICCS	No (phosphoric acid ester amine salt)		
USA - TSCA	TSCA Inventory 'Active' substance(s) (white mineral oil (petroleum); benzene); No (phosphoric acid ester amine salt)		

# Page 12 of 13 Issue Date: 23/12/2022 LE1302 DUOLEC Vari-Purpose Gear Lubricant Print Date: 29/10/2024

National Inventory	Status		
Taiwan - TCSI	Yes		
Mexico - INSQ	No (phosphoric acid ester amine salt)		
Vietnam - NCI	Yes		
Russia - FBEPH	No (phosphoric acid ester amine salt)		
Legend:	Yes = All CAS declared ingredients are on the inventory No = One or more of the CAS listed ingredients are not on the inventory. These ingredients may be exempt or will requ registration.		

#### **SECTION 16 Other information**

Revision Date	23/12/2022
Initial Date	15/12/2009

## **SDS Version Summary**

Version No: 8.1

Version	Date of Update	Sections Updated
7.1	01/11/2019	One-off system update. NOTE: This may or may not change the GHS classification
8.1	23/12/2022	Classification review due to GHS Revision change.

#### Other information

Classification of the preparation and its individual components has drawn on official and authoritative sources as well as independent review by the Chemwatch Classification committee using available literature references.

The SDS is a Hazard Communication tool and should be used to assist in the Risk Assessment. Many factors determine whether the reported Hazards are Risks in the workplace or other settings. Risks may be determined by reference to Exposures Scenarios. Scale of use, frequency of use and current or available engineering controls must be considered.

#### **Definitions and abbreviations**

- ▶ PC TWA: Permissible Concentration-Time Weighted Average
- ▶ PC STEL: Permissible Concentration-Short Term Exposure Limit
- IARC: International Agency for Research on Cancer
- ▶ ACGIH: American Conference of Governmental Industrial Hygienists
- ▶ STEL: Short Term Exposure Limit
- ► TEEL: Temporary Emergency Exposure Limit。
- ▶ IDLH: Immediately Dangerous to Life or Health Concentrations
- ES: Exposure Standard
- OSF: Odour Safety Factor
- NOAEL: No Observed Adverse Effect Level
- ▶ LOAEL: Lowest Observed Adverse Effect Level
- ► TLV: Threshold Limit Value
- ▶ LOD: Limit Of Detection
- ▶ OTV: Odour Threshold Value
- ▶ BCF: BioConcentration Factors
- ▶ BEI: Biological Exposure Index
- ▶ DNEL: Derived No-Effect Level
- ▶ PNEC: Predicted no-effect concentration
- ▶ AIIC: Australian Inventory of Industrial Chemicals
- ▶ DSL: Domestic Substances List
- ▶ NDSL: Non-Domestic Substances List
- ▶ IECSC: Inventory of Existing Chemical Substance in China
- ▶ EINECS: European INventory of Existing Commercial chemical Substances
- ▶ ELINCS: European List of Notified Chemical Substances
- NLP: No-Longer Polymers
- ▶ ENCS: Existing and New Chemical Substances Inventory
- ▶ KECI: Korea Existing Chemicals Inventory
- ▶ NZIoC: New Zealand Inventory of Chemicals
- ▶ PICCS: Philippine Inventory of Chemicals and Chemical Substances
- TSCA: Toxic Substances Control Act
- ▶ TCSI: Taiwan Chemical Substance Inventory
- ▶ INSQ: Inventario Nacional de Sustancias Químicas
- ▶ NCI: National Chemical Inventory
- ▶ FBEPH: Russian Register of Potentially Hazardous Chemical and Biological Substances

#### This document is copyright

Apart from any fair dealing for the purposes of private study, research, review or criticism, as permitted under the Copyright Act, no part may be reproduced by any process without written permission from CHEMWATCH.

Chemwatch: 22-7647 Version No: 8.1 Page **13** of **13** 

LE1302 DUOLEC Vari-Purpose Gear Lubricant

Issue Date: 23/12/2022 Print Date: 29/10/2024

TEL (+61 3) 9572 4700.